



TRIFACTA

Planning Guide

Version: 6.0.2
Doc Build Date: 07/11/2019

Copyright © Trifacta Inc. 2019 - All Rights Reserved. CONFIDENTIAL

These materials (the “Documentation”) are the confidential and proprietary information of Trifacta Inc. and may not be reproduced, modified, or distributed without the prior written permission of Trifacta Inc.

EXCEPT AS OTHERWISE PROVIDED IN AN EXPRESS WRITTEN AGREEMENT, TRIFACTA INC. PROVIDES THIS DOCUMENTATION AS-IS AND WITHOUT WARRANTY AND TRIFACTA INC. DISCLAIMS ALL EXPRESS AND IMPLIED WARRANTIES TO THE EXTENT PERMITTED, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT AND FITNESS FOR A PARTICULAR PURPOSE AND UNDER NO CIRCUMSTANCES WILL TRIFACTA INC. BE LIABLE FOR ANY AMOUNT GREATER THAN ONE HUNDRED DOLLARS (\$100) BASED ON ANY USE OF THE DOCUMENTATION.

For third-party license information, please select **About Trifacta** from the User menu.

This page intentionally left blank. Please remove prior to publication.

- 1. *Install Preparation . . 4*
 - 1.1 *Pre-Install Checklist . . 4*
 - 1.2 *Product Limitations 10*
 - 1.3 *System Requirements 13*
 - 1.4 *Sizing Guidelines . 20*
 - 1.5 *System Ports . 22*
 - 1.6 *System Dependencies 24*
 - 1.7 *Desktop Requirements 27*
 - 1.8 *Supported File Formats . 31*
 - 1.9 *Required Users and Groups . 34*
 - 1.10 *Prepare Hadoop for Integration with the Platform . 37*

Install Preparation

Before you begin installing and deploying Trifacta® Wrangler Enterprise, you should review these topics on preparing your environment for Trifacta software installation and integration with your enterprise infrastructure.

Topics:

- *Pre-Install Checklist*
- *Product Limitations*
- *System Requirements*
- *Sizing Guidelines*
- *System Ports*
- *System Dependencies*
- *Desktop Requirements*
- *Supported File Formats*
- *Required Users and Groups*
- *Prepare Hadoop for Integration with the Platform*

Pre-Install Checklist

Contents:

- *Trifacta node*
 - *Operating System*
 - *Cores*
 - *RAM Memory*
 - *Disk Space*
 - *Internet Access*
 - *Databases*
 - *Cloud Infrastructure*
 - *AWS*
 - *Azure*
 - *Hadoop Cluster*
 - *Cluster Type and Version*
 - *Number of data nodes*
 - *Data node - number of cores*
 - *Data node - memory*
 - *Upgrade plans*
 - *Hadoop Cluster Details*
 - *Hadoop Cluster Security*
 - *Firewall*
 - *Connectivity*
 - *Primary backend storage*
 - *Hive*
 - *Redshift*
 - *Relational Connections*
 - *Desktop Environments*
 - *Extras*
-

Before you begin installing Trifacta® Wrangler Enterprise, please review the following checklist to verify that the applicable items are available and ready to deploy with the software.

NOTE: Enablement of specific features or integration with external sources may have additional requirements listed in any referenced content.

Trifacta node

The node where the Trifacta software is to be installed should meet the following requirements:

Item	Description	Status or Value
Operating System	The operating system on the node must be one of the supported 64-bit versions. For more information, see <i>System Requirements</i> .	
Cores	Minimum of four cores	
RAM Memory	Minimum of 16 GB dedicated	
Disk Space	Minimum of 20 GB	
Internet Access	If your data sources are available over an Internet connection, the platform must be permitted to use that connection.	
Databases	<p>The Trifacta databases can be installed in PostgreSQL or MySQL.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"><p>NOTE: By default, the databases are installed on the local server. They can be installed on a remote node as needed.</p></div>	

Cloud Infrastructure

Trifacta Wrangler Enterprise can be installed within your enterprise infrastructure or optionally on one of the following cloud-based infrastructures.

Item	Description	Status or Value
AWS	<p>Trifacta Wrangler Enterprise is to be installed on Amazon Web Services (AWS) infrastructure.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"><p>Tip: Trifacta Wrangler Enterprise can be installed from the Amazon Marketplace with a number of configuration steps automatically performed for you. For more information, please visit <i>Wrangler Enterprise</i>.</p></div>	

Azure	<p>Trifacta Wrangler Enterprise is to be installed on Microsoft Azure infrastructure.</p> <div style="border: 1px solid green; padding: 5px; margin: 10px 0;"> <p>Tip: Trifacta Wrangler Enterprise can be installed from the Azure Marketplace with a number of configuration steps automatically performed for you. For more information, please visit <i>Trifacta Wrangler Enterprise</i>.</p> </div>	
--------------	---	--

Hadoop Cluster

If your instance of Trifacta Wrangler Enterprise must integrate with a Hadoop-based cluster, please verify the following:

NOTE: The number of nodes in your cluster and the number of cores and amount of memory on each data node can affect the performance of running jobs on the cluster. If you have questions about cluster size, please contact *Trifacta Customer Success Services*.

Item	Description	Status or Value
Cluster Type and Version	<p>Supported types of Hadoop clusters:</p> <ul style="list-style-type: none"> • Cloudera - For supported version information, see <i>Supported Deployment Scenarios for Cloudera</i> • Hortonworks - For supported version information, see <i>Supported Deployment Scenarios for Hortonworks</i> • EMR (AWS only) - For supported version information, see <i>Configure for EMR</i>. • HDInsight (Azure only) - For supported version information, see <i>Configure for HDInsight</i>. • Azure Databricks (Azure only) - For supported version information, see <i>Configure for Azure Databricks</i>. 	
Number of data nodes	Total number of data nodes.	
Data node - number of cores	Number of cores on each data node.	
Data node - memory	Volume of RAM memory (GB) on each data node.	
Upgrade plans	If there are planned upgrades to the cluster, please review the list of supported versions to verify that the new version is supported within the timeframe of your upgrade plans.	

Hadoop Cluster Details

During installation and configuration, you may need to specify the following configuration information to successfully integrate Trifacta Wrangler Enterprise with your cluster.

Item	Description	Status or Value
Namenode host	Host name of the namenode on the cluster	
Namenode port	Port number of the namenode on the cluster	
Secondary namenode host	Host name for the secondary namenode for the cluster <div style="border: 1px solid black; border-radius: 10px; padding: 5px; width: fit-content; margin: 10px auto;"> <p>NOTE: This value is only required if high availability is enabled on the cluster.</p> </div>	
Secondary namenode port	Port number for the secondary namenode on the cluster <div style="border: 1px solid black; border-radius: 10px; padding: 5px; width: fit-content; margin: 10px auto;"> <p>NOTE: This value is only required if high availability is enabled on the cluster.</p> </div>	
Namenode Service name	Name for the namenode service <div style="border: 1px solid black; border-radius: 10px; padding: 5px; width: fit-content; margin: 10px auto;"> <p>NOTE: This value is only required if high availability is enabled on the cluster.</p> </div>	
ResourceManager host	Host name for the ResourceManager on the cluster	
ResourceManager port	Port number for the ResourceManager on the cluster	
Secondary ResourceManager host	Host name for the secondary ResourceManager on the cluster <div style="border: 1px solid black; border-radius: 10px; padding: 5px; width: fit-content; margin: 10px auto;"> <p>NOTE: This value is only required if high availability is enabled on the cluster.</p> </div>	
Secondary ResourceManager port	Port number for the secondary ResourceManager on the cluster <div style="border: 1px solid black; border-radius: 10px; padding: 5px; width: fit-content; margin: 10px auto;"> <p>NOTE: This value is only required if high availability is enabled on the cluster.</p> </div>	
Hive host	Host name for the Hive server on the cluster. For more information, see <i>Configure for Hive</i> in the Configuration Guide.	
Hive port	Port number for the Hive server on the cluster. For more information, see <i>Configure for Hive</i> in the Configuration Guide.	

HttpFS host	Host name for the HttpFS server on the cluster. NOTE: This value is only required if high availability is enabled on the cluster.	
HttpFS port	Port number for the HttpFS server on the cluster. NOTE: This value is only required if high availability is enabled on the cluster.	

Hadoop Cluster Security

Item	Description	Status or Value
HDFS Service user	By default, the platform uses the <code>trifacta</code> user to integrate with the cluster. When Kerberos is enabled, this user is used to impersonate other users on the cluster. For more information on required users, see <i>Required Users and Groups</i> .	
HDFS transfer encryption	Optionally, the cluster can be configured to use SSL/TLS on data transfer for HDFS. On the cluster, this setting is defined using the <code>dfs.encrypt.data.transfer</code> setting.	
SSL on HTTP endpoints	Is encryption applied to the WebHDFS /HttpFS endpoints?	
Kerberos	Cluster has been enabled for Kerberos. For more information on the integration, see <i>Configure for Kerberos Integration</i> in the Configuration Guide.	
KDC	Name for the Key Data Center for Kerberos. For more information on the integration, see <i>Configure for Kerberos Integration</i> in the Configuration Guide.	
Kerberos realm	Realm for the Key Data Center for Kerberos. For more information, see <i>Configure for Kerberos Integration</i> in the Configuration Guide.	

Firewall

Item	Description	Status or Value
------	-------------	-----------------

Firewall between users and cluster	If a firewall is present between users and the cluster, the default web application port must be opened for user access. See below.	
Web application port	By default, the Trifacta application is available on port 3005. As needed, this value can be modified. For more information, see <i>System Ports</i> .	

Connectivity

Trifacta Wrangler Enterprise supports read-only or read-write integration with the following datastores.

Item	Description	Status or Value
Primary backend storage	The following primary storage environments are supported: HDFS or S3. For more information, see <i>Set Base Storage Layer</i> in the Configuration Guide.	
Hive	For more information, see <i>Configure for Hive</i> in the Configuration Guide.	
Redshift	For more information, see <i>Create Redshift Connections</i> in the Configuration Guide.	
Relational Connections	Supported connections include Oracle, SQL Server, Teradata, Tableau, Salesforce, and more. For more information, see <i>Connection Types</i> .	

Desktop Environments

The following requirements apply to end-user desktop environments.

Item	Description	Status or Value
Google Chrome version	The application requires that users connect using a version of Google Chrome. <div style="border: 1px solid gray; padding: 10px; margin: 10px 0;"> <p>NOTE: Trifacta Wrangler Enterprise supports the latest stable version of Google Chrome and the two prior versions, at the time that any release of the product is generally available.</p> </div> For a list of supported versions, see <i>Desktop Requirements</i> .	

Enterprise Application	<p>If Google Chrome is not available, users can connect to the application using a custom desktop application.</p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p>NOTE: The Enterprise application can be deployed to Windows-based desktops only.</p> </div> <p>For more information, see <i>Install for Wrangler Enterprise Application</i> in the Install Guide.</p>	
-------------------------------	---	--

Extras

Deployment or use of these features requires additional configuration or development external to the application. Related content may not be available in printed format.

Item	Description	Status or Value
Cluster Compression	<p>The platform can integrate with clusters that are compressed using Bzip2, Gzip, or Snappy. For more information, see <i>Enable Integration with Compressed Clusters</i> in the Configuration Guide.</p>	
Single Sign-On	<p>The application can integrate with the following Single Sign-On solutions:</p> <ul style="list-style-type: none"> • AD-LDAP - For more information, see <i>Configure SSO for AD-LDAP</i> in the Configuration Guide. • Azure AD (Azure only) - For more information, see <i>Configure SSO for Azure AD</i> in the Configuration Guide. 	
SSL for the platform	<p>You can apply an SSL certificate to the Trifacta node for secure communications. For more information, see <i>Install SSL Certificate</i> in the Install Guide.</p>	
API	<p>You can manage aspects of your flows, datasets, and connections through publicly available Application Protocol Interfaces (APIs). For more information, see <i>API Reference</i> in the Developer's Guide.</p>	
UDF	<p>You can create custom user-defined functions for deployment into the platform.</p> <p>For more information on the list of available functions, see <i>Language Index</i> in the Language Reference Guide.</p> <p>For more information on UDFs, see <i>User-Defined Functions</i> in the Developer's Guide.</p>	

Product Limitations

Contents:

- *Sampling*
- *Internationalization*

- *Size Limits*
 - *Sample Size Limits*
 - *Job Size Limits*
 - *Limitations by Integration*
 - *General*
 - *LDAP*
 - *Hadoop*
 - *Amazon AMI*
 - *Amazon EMR*
 - *Microsoft Azure*
 - *S3*
 - *Redshift*
 - *Hive*
 - *Spark*
 - *JDBC*
 - *Other Limitations*
-

This section covers key known limitations of Trifacta® Wrangler Enterprise.

NOTE: This list of limitations should not be considered complete.

Sampling

- Sample sizes are defined by parameter for each available running environment. See *Sample Size Limits* be low.
-
-
- All values displayed or generated in the application are based on the currently displayed sample.
 - Transforms that generate new data may not factor values that are not present in the current sample.
 - When the job is executed, transforms are applied across all rows and values in the source data.
 - Transforms that make changes based on data values, such as `header` and `valuestocols`, will still be configured according to sample data at the time of that the step was added, instead at execution time. For example, all of the values detected in the sample are used to determine the columns of a `valuestocols` transform step based on the selected sample when the step was added.
- Random samples are derived from up to the first 1 GB of the source file.
 - Data from later parts of a multi-part file may not be included in the sample.
 - For more information, see *Samples Panel*.

Internationalization

- The product supports a variety of global file encoding types for import. For more information, see *Configure Global File Encoding Type*.
- Within the application, UTF-8 encodings are displayed.
 - Limited set of characters allowed in column names.
 - Header does not support all UTF-8 characters.
 - Emoji are not supported in data wrangling operations.
 - Umlauts and other international characters are not supported when filtering datasets in browsers of external datastores.
- UTF-8 is generated in output.
 - Some international characters are presented incorrectly in the output.
- States and Zip Code Column Types and the corresponding maps in visual profiling apply only to the United States.

- UTF-32 encoding is not supported

NOTE: Some functions do not correctly account for multi-byte characters. Multi-byte metadata values may not be consistently managed.

Size Limits

Sample Size Limits

Defaults for each running environment:

- For the Trifacta Photon running environment, samples are limited to 10 MB.
- For more information on changing sample sizes, see *Running Environment Options*.

Job Size Limits

Execution on a Spark running environment is recommended for any files over 5GB in net data size, including join keys.

Limitations by Integration

General

The product requires definition of a base storage layer, which can be HDFS or S3 for this version. This base storage layer must be defined during install and cannot be changed after installation. See *Set Base Storage Layer*.

LDAP

- If LDAP integration is enabled, the LDAP user [`ldap.user` (default=`trifacta`)] should be created in the same realm.
- See *Configure SSO for AD-LDAP*.

Hadoop

- Trifacta Wrangler Enterprise requires an integration with a working Hadoop cluster.
- See *Running Environment Options*.

Amazon AMI

- For more information, see *Install from AWS Marketplace*.

Amazon EMR

- For more information, see *Install from AWS Marketplace*.
- For more information, see *Configure for EMR*.

Microsoft Azure

- For more information, see *Configure for Azure*.

S3

- S3 integration is supported only over AWS-hosted instances of S3.
- Oracle Java Runtime 1.8 must be installed on the node hosting the product.
- Writing to S3 requires use of S3 as the base storage layer. For more information, see *Set Base Storage Layer*.
- When publishing single files to S3, you cannot apply an `append` publishing action.

Redshift

None.

Hive

- Only HiveServer2 is supported.
- You can create only one connection of this type.
- When reading from a partitioned table, the product reads from all partitions, which impacts performance.
- For more information, see *Configure for Hive*.

Spark

- None.

JDBC

- The product supports explicit versions of each JDBC source.
 - Some additional installation may be required.
 - See *Enable Relational Connections*.
- Jobs for JDBC sources must be executed on the Trifacta Photon running environment.
- Writing to JDBC sources is not supported in this release.

Other Limitations

- **File Formats:** Limitations may apply to individual file formats. See *Supported File Formats*.
- **Data Type Conversions:** There are some limitations on the data types that can be imported for individual file formats and sources. Some sources are read-only. See *Type Conversions*.

System Requirements

Contents:

- *Edge Node Requirements*
 - *Hardware Requirements*
 - *Operating System Requirements*
 - *Database Requirements*
 - *Other Software Requirements*

- *Root User Access*
 - *SSL Access*
 - *Internet Access*
 - *Hadoop Cluster Requirements*
 - *Supported Hadoop Distributions*
 - *Node Requirements*
 - *Hadoop Component Access*
 - *Hadoop System Ports*
 - *Site Configuration Files*
 - *Security Requirements*
 - *Cluster Configuration*
 - *User Requirements*
 - *I/O Requirements*
-

This section contains hardware and software requirements for successful installation of Trifacta® Wrangler Enterprise.

Edge Node Requirements

If the Trifacta platform is installed in a Hadoop cluster, the platform is typically installed on an edge node of the cluster.

NOTE: The Trifacta platform does not require edge node installation.

Hardware Requirements

Minimum hardware:

Item	Required
Number of cores	8 cores
RAM	64 GB
	<div style="border: 1px solid #ccc; border-radius: 10px; padding: 5px; width: fit-content; margin: 0 auto;"> <p>NOTE: The platform requires 12GB of dedicated RAM to start and perform basic operations.</p> </div>
Disk space to install software	4 GB
Total free disk space	16 GB
	<p>Space requirements by volume:</p> <ul style="list-style-type: none"> • /opt - 10 GB • /var - Remainder

Recommended hardware:

Item	Recommended
Number of cores	16 cores

RAM	128 GB NOTE: The platform requires 12GB of dedicated RAM to start and perform basic operations.
Disk space to install software	16 GB
Total free disk space	100 GB Space requirements by volume: <ul style="list-style-type: none"> • /opt - 10 GB • /var - Remainder

Operating System Requirements

The following operating systems are supported for the Trifacta node.

NOTE: The Trifacta platform requires 64-bit versions of any supported operating system.

- CentOS 6.4 - 6.x, 7.1 - 7.4
- RHEL 6.4 - 6.x, 7.1 - 7.4

NOTE: If you are installing on CentOS/RHEL 7.1, you must be connected to an online repository for some critical updates. Offline installation is not supported for these operating system distributions.

NOTE: For security reasons, RHEL 7.3 is not supported for installation of Release 5.0 or later of the Trifacta platform. Please upgrade to RHEL 7.4 or a later supported release.

Tip: Disabling SELinux on the Trifacta node is recommended. However, if security policies require it, you may need to apply some changes to the environment. For more information on SELinux, see *Install from AWS Marketplace*.

- Ubuntu 14.04 (codename Trusty) and 16.04 (codename Xenial)

NOTE: For Ubuntu installations, some packages must be manually installed. Instructions are provided later in the process.

NOTE: During normal operations, the platform may maintain a high number of open files, which may exceed the default limit defined by the operating system. Before you begin using the system, you should raise this limit to 64000. For more information on raising the ulimit, see *Miscellaneous Configuration*.

NOTE: If you are enabling SSO and want to use an Apache Server as a reverse proxy for the Trifacta node, you may need to upgrade to Apache Server. See *Configure SSO for AD-LDAP*.

For more information on RPM dependencies, see *System Dependencies*.

Database Requirements

The following database versions are supported by the Trifacta platform for storing metadata and the user's Wrangle recipes.

NOTE: One of these supported versions must be installed on the Trifacta node.

Supported versions:

- PostgreSQL 9.6
- MySQL 5.7 Community

NOTE: If you are installing the databases into MySQL, you must download and install the MySQL Java driver onto the Trifacta node. For more information, see *Install Databases for PostgreSQL*.

NOTE: MySQL 5.7 is not supported for installation in Amazon RDS.

NOTE: H2 database type is used for internal testing. It is not a supported database.

For more information on installing and configuring the database, see *Install Databases*.

Other Software Requirements

The following software components must be present.

Java

Tip: Where possible, you should install the same version of Java on the Trifacta node and on the cluster with which you are integrating.

- Java 1.8

NOTE: There are additional requirements related to Java JDK listed in the Hadoop Components section listed below.

NOTE: If you are integrating your Trifacta instance with S3, you must install the Oracle JRE 1.8 onto the Trifacta node. No other version of Java is supported for S3 integration. See *Enable S3 Access*.

NOTE: OpenJDK 1.8 is officially supported. It must be installed on the Trifacta node during the installation process. See *Install Enterprise on CentOS and RHEL*.

Other Software

NOTE: For Ubuntu installations, the following packages must be manually installed using Ubuntu-specific versions. Instructions and version numbers are provided later in the process.

- NginX 1.12.2
- NodeJS 10.13.0

Root User Access

Installation must be executed as the root user on the Trifacta node.

SSL Access

(Optional) If users are connecting to the Trifacta platform, an SSL certificate must be created and deployed. See *Install SSL Certificate*.

Internet Access

(Optional) Internet access is not required for installation or operation of the platform. However, if the server does not have Internet access, you must acquire additional software as part of the disconnected install. For more information, see *Install Dependencies without Internet Access*.

Hadoop Cluster Requirements

The following requirements apply if you are integrating the Trifacta platform with an enterprise Hadoop cluster.

NOTE: For general guidelines on sizing the cluster, see *Sizing Guidelines*.

NOTE: If you have upgrades to the Hadoop cluster planned for the next year, you should review those plans with Support prior to installation. For more information, please contact *Trifacta Support*.

Supported Hadoop Distributions

NOTE: The Trifacta platform only supports the latest major release and its minor releases of each distribution.

The Trifacta platform only supports the versions of any required components included in a supported distribution. Even if they are upgraded components, use of non-default versions of required components is not supported.

The Trifacta platform supports the following minimum Hadoop distributions:

Vendor	Supported Versions	Link
--------	--------------------	------

Cloudera	<ul style="list-style-type: none"> • CDH 6.2 (Release 6.0.1 and later) • CDH 6.1 (Release 6.0.1 and later) • CDH 6.0 Recommended <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p>NOTE: CDH 6.x requires that you use the native Spark libraries provided by the cluster. Additional configuration is required. For more information, see <i>Configure for Spark</i>.</p> </div> <ul style="list-style-type: none"> • CDH 5.16 (Release 6.0.1 and later) • CDH 5.15 Recommended • CDH 5.14 	<i>Supported Deployment Scenarios for Cloudera</i>
Hortonworks	<ul style="list-style-type: none"> • HDP 3.1 (Release 6.0.1 and later) • HDP 3.0 Recommended <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p>NOTE: HDP 3.x requires that you use the native Spark libraries provided by the cluster. Additional configuration is required. For more information, see <i>Configure for Spark</i>.</p> </div> <ul style="list-style-type: none"> • HDP 2.6 • HDP 2.5 	<i>Supported Deployment Scenarios for Hortonworks</i>
EMR	See <i>Configure for EMR</i> .	
HDInsight	See <i>Configure for HDInsight</i> .	
Azure Databricks	See <i>Configure for Azure Databricks</i> .	

Node Requirements

Each cluster node must have the following software:

- Java JDK 1.8 (some exceptions may be listed below)

Hadoop Component Access

The Trifacta deployment must have access to the following.

Java and Spark version requirements

The following matrix identifies the supported versions of Java and Spark on the Hadoop cluster.

NOTE: In the next release of Trifacta Wrangler Enterprise after Release 6.0, the use of Java 1.7 will no longer be supported. The platform will not work with this version of Java. Please upgrade the Trifacta node and the cluster to use Java 1.8.

Tip: Where possible, you should install the same version of Java on the Trifacta node and on the cluster with which you are integrating.

Notes:

- Java must be installed on each node of the cluster.
- If you are integrating with an EMR cluster, there are specific version requirements for EMR. See *Configure for Spark*.
- By default, Cloudera may be installed with Java JDK 1.7 or earlier. If you are upgrading to Java JDK 1.8, you must do so on each node of the cluster. For more information, see https://www.cloudera.com/documentation/enterprise/latest/topics/cdh_ig_jdk_installation.html.
- The versions of Java on the Trifacta node and the Hadoop cluster do not have to match.

	Spark 2.1	Spark 2.2	Spark 2.3	Spark 2.4
Java 1.7	Supported.	Not supported.	Not supported.	Not supported.
Java 1.8	Supported.	Required.	Required.	Required.

Other components

- HDFS Namenode
 - WebHDFS

NOTE: In HDFS, Append Mode must be enabled. See *Prepare Hadoop for Integration with the Platform*.

NOTE: If you are enabling high availability failover, you must use HttpFS, instead of WebHDFS. See *Enable Integration with Cluster High Availability*.

- For Map Reduce 1:

NOTE: As of Release 2.7, Map Reduce 1 has been deprecated. For more information, please see *End of Life and Deprecated Features*.

- JobTracker is running.
- For YARN:
 - ResourceManager is running.
 - ApplicationMaster's range of ephemeral ports are open to the Trifacta node.
- HiveServer2:
 - HiveServer2 is supported for metadata publishing. Additional configuration is required. See *Configure for Hive*.
 - WebHCat is not supported.

Hadoop System Ports

For more information, see *System Ports*.

Site Configuration Files

Hadoop cluster configuration files must be copied into the Trifacta deployment. It is especially important in a YARN deployment. See *Configure for Hadoop*.

Security Requirements

- **Kerberos supported:**
 - If Kerberos is enabled, a keytab file must be accessible to the Trifacta platform.
 - See *Configure for Kerberos Integration*.
- **If Kerberos and secure impersonation are not enabled:**
 - A user [`hadoop.user` (default=`trifacta`)] must be created on each node of the Hadoop cluster.
 - A directory [`hadoop.dir` (default=`trifacta`)] must be created on the cluster.
 - The user [`hadoop.user`] must have full access to the directory, which enables storage of the transformation recipe back into HDFS.
 - See *Configure for Hadoop*.

Cluster Configuration

For more information on integration with Hadoop, see *Prepare Hadoop for Integration with the Platform*.

User Requirements

Users must access the Trifacta platform through the Google Chrome browser. For more information on user system requirements, see *Desktop Requirements*.

I/O Requirements

See *Supported File Formats*.

Sizing Guidelines

Contents:

- *Requirements for the Trifacta node*
- *Enterprise Hadoop*
- *Amazon*
 - *Amazon Marketplace AMI*
 - *Amazon EMR*
- *Microsoft Azure*

This section provides general guidelines for cluster sizing and node requirements for effective use of the Trifacta® platform.

NOTE: These guidelines are rough estimates of what should provide satisfactory performance. You should review particulars of the variables listed below in detail prior to making recommendations or purchasing decisions.

Requirements for the Trifacta node

See *System Requirements*.

Enterprise Hadoop

All compute nodes on the cluster (Hadoop NodeManager nodes) should have identical capabilities. Avoid mixing and matching nodes of different capabilities.

Primary variables affecting cluster size:

- Data volume
- Number of concurrent jobs

In the following table, you can review the recommended number of worker nodes in the cluster based on the data volume and the number of concurrent jobs. Table data assumes that each compute node has 16 compute cores (2 x 8 cores), 128GB of RAM and 8TB of disk, with nodes connected via 10 gigabit Ethernet (GbE).

Data Volume \ Number of concurrent jobs	1	5	10	25
1 GB or less	1	1	1	2
10 GB	1	1	2	5
25 GB	1	2	5	10
50 GB	1	5	10	25
100 GB	2	10	20	50
250 GB	5	25	50	125
500 GB	10	50	100	250
1000 GB (1 TB)	20	100	200	500

Additional variables affecting cluster size:

- If you are working with compressed or binary formats, you should use the expanded sizes for your data volume estimates.
- Some workloads are more compute- or memory-intensive and may increase the required number of nodes or capabilities of each node. These include:
 - Scripts with complex steps such as joins (particularly those between large datasets) and sorts
 - Lengthy scripts

Amazon

Amazon Marketplace AMI

Amazon Marketplace installations support a limited range of installation options for the AMI. For more information, see the install guide available through the Marketplace for Trifacta Wrangler Pro.

Amazon EMR

NOTE: The sizing guidelines listed for Enterprise Hadoop above provide a good estimate for sizing capacity and upper bounds for EMR-based cluster scaling.

For additional details on sizing your EMR cluster, please contact *Trifacta Customer Success Services*.

Microsoft Azure

Azure Marketplace installations support a limited range of installation options, based on the type of cluster integration.

Cluster Type	Description
--------------	-------------

HDI	Please use the Enterprise Hadoop guidelines listed previously. For more information on this integration, see <i>Configure for HDInsight</i> .
Azure Databricks	Please review the Enterprise Hadoop guidelines with <i>Trifacta Customer Success Services</i> . For more information on this integration, see <i>Configure for Azure Databricks</i> .

For more information, see the install guide available through the Marketplace for Trifacta Wrangler Enterprise.

System Ports

Contents:

- *Trifacta® node Ports*
 - *Internal Service Ports*
 - *Database Ports*
 - *Client Browser Ports*
- *Hadoop Ports*
 - *Firewall Ports for Hadoop*
- *EMR Ports*

Trifacta® node Ports

Depending on the components enabled or integrated with your instance of the platform, the following ports must be opened on the Trifacta node.

Internal Service Ports

Component	Port
Nginx Proxy	3005
Trifacta application	3006
Java UDF Service	3008
Spark Job Service	4007
Supervisor	4421
ML-Service	5000
Data Service	41912
Batch Job Runner	41920
VFS Service	41913
Time-based trigger service port	43033
Scheduling service port	43143

Database Ports

Component	Port
-----------	------

Postgres (default)	5432
	<p>NOTE: By default, PostgreSQL and the platform use port 5432 for communication. If that port is not available at install/upgrade time, the next available port is used, which is typically 5433. This change may occur if a previous version of PostgreSQL is on the same server. When a non-default port number is used, the platform must be configured to use it. For more information, see <i>Change Database Port</i>.</p>
MySQL	3306

Client Browser Ports

By default, the web client uses port 3005.

NOTE: Any client firewall software must be configured to enable access on this port.

This port can be changed. For more information, see *Change Listening Port*.

Hadoop Ports

If Trifacta Wrangler Enterprise is integrated with a Hadoop cluster, the Trifacta node must have access to the following Hadoop components. Their default ports are listed below:

NOTE: These ports vary between installations. Please verify your environment's ports.

Hadoop Component	Default Port
HDFS Namenode	Cloudera/HDP: 8020
HDFS Datanode	50020
	<p>NOTE: The Trifacta node must be able to access this port on all HDFS datanodes of the cluster.</p>
HttpFS	14000
WebHDFS	Cloudera/HDP: 50070
YARN ResourceManager	Cloudera: 8032 HDP: 8050
JobTracker	Cloudera/HDP: 8021
	<p>NOTE: As of Release 2.7, Map Reduce 1 has been deprecated. For more information, please see <i>End of Life and Deprecated Features</i>.</p>
HiveServer2 (optional)	TCP connection: 10000 HTTP connection: 10001
Hive Metastore (optional)	9083

Firewall Ports for Hadoop

If the Trifacta node is on a different network from the Hadoop cluster, please verify that these additional ports are opened on the firewall.

Hadoop Component	Default Port
YARN Resourcemanager Scheduler	8030
YARN Resourcemanager Admin	8033
YARN Resourcemanager WebApp	8088
YARN Nodemanager WebApp	8042
YARN Timeline Service	8188
MapReduce JobHistory Server	10020
HDFS DataNode	50010

For additional details, please refer to the documentation provided with your Hadoop distribution.

EMR Ports

If you are integrating with an EMR cluster, please verify that the following nodes and ports are available to the Trifacta node.

EMR Component	Port
EMR master node	8088

System Dependencies

Contents:

- *Direct Dependencies*
 - *CentOS/Redhat 6*
 - *CentOS/Redhat 7*
 - *Ubuntu 14.04*
 - *Ubuntu 16.04*
- *Direct and Indirect Dependencies*
 - *CentOS/Redhat 6*
 - *CentOS/Redhat 7*
 - *Ubuntu 14.04 / Ubuntu 16.04*

The following direct and indirect dependencies apply to the Trifacta software that is installed on the edge node for each supported version of the operating system.

NOTE: When dependencies are acquired for versions of Ubuntu, the operating system grabs the latest version, even if it is later than the version on which the software is dependent. In some cases, this mismatch can result in installation errors, which can be fixed by manually installing the dependency with the correct version.

Direct Dependencies

These direct dependencies are packaged with the Trifacta® installer.

CentOS/Redhat 6

python-supervisor = 3.0

nodejs = 2:10.13.0

nginx = 1.12.2-1

gzip = 1.3.12-22

bzip2 = 1.0.5-7

openldap-clients

CentOS/Redhat 7

supervisor = 3.1.3

nodejs = 2:10.13.0

nginx = 1:1.12.2-1

gzip = 1.5-8

bzip2 = 1.0.6-13

openldap-clients

Ubuntu 14.04

python-supervisor = 3.0

nodejs = 10.13.0-1nodesource1

nginx = 1.12.2-1~trusty

rlwrap = 0.37-5

gzip = 1.4-1ubuntu2

bzip2 = 1.0.6-1

ldap-utils

Ubuntu 16.04

supervisor = 3.2.0-2

nodejs = 10.13.0-1nodesource1

nginx = 1.12.2-1~xenial

rlwrap = 0.37-5

gzip = 1.4-1ubuntu2

bzip2 = 1.0.6-1

ldap-utils

Direct and Indirect Dependencies

This full list of dependencies is applied during online installs or is included in the offline install package provided to you:

CentOS/Redhat 6

alsa-lib-1.1.0-4.el6.x86_64.rpm
fontconfig-2.8.0-5.el6.x86_64.rpm
freetype-2.3.11-17.el6.x86_64.rpm
giflib-4.1.6-3.1.el6.x86_64.rpm
java-1.8.0-openjdk-1.8.0.121-0.b13.el6_8.x86_64.rpm
java-1.8.0-openjdk-devel-1.8.0.121-0.b13.el6_8.x86_64.rpm
java-1.8.0-openjdk-headless-1.8.0.121-0.b13.el6_8.x86_64.rpm
jpackage-utils-1.7.5-3.16.el6.noarch.rpm
libICE-1.0.6-1.el6.x86_64.rpm
libSM-1.2.1-2.el6.x86_64.rpm
libX11-1.6.3-2.el6.x86_64.rpm
libX11-common-1.6.3-2.el6.noarch.rpm
libXau-1.0.6-4.el6.x86_64.rpm
libXext-1.3.3-1.el6.x86_64.rpm
libXfont-1.5.1-2.el6.x86_64.rpm
libXi-1.7.4-1.el6.x86_64.rpm
libXrender-0.9.8-2.1.el6_8.1.x86_64.rpm
libXtst-1.2.2-2.1.el6.x86_64.rpm
libfontenc-1.1.2-3.el6.x86_64.rpm
libjpeg-turbo-1.2.1-3.el6_5.x86_64.rpm
libpng-1.2.49-2.el6_7.x86_64.rpm
libxcb-1.11-2.el6.x86_64.rpm
make-3.81-23.el6.x86_64.rpm
nginx-1.6.2-1.el6ngx.x86_64.rpm
nodejs-10.13.0-1nodesource.el6.x86_64.rpm
nspr-4.11.0-1.el6.x86_64.rpm
nss-3.21.3-2.el6_8.x86_64.rpm
nss-softokn-3.14.3-23.3.el6_8.x86_64.rpm
nss-softokn-freebl-3.14.3-23.3.el6_8.x86_64.rpm
nss-sysinit-3.21.3-2.el6_8.x86_64.rpm
nss-tools-3.21.3-2.el6_8.x86_64.rpm
nss-util-3.21.3-1.el6_8.x86_64.rpm
openldap-clients-2.4.40-16.el6.x86_64
openssl-1.0.1e-48.el6_8.4.x86_64.rpm
pkgconfig-0.23-9.1.el6.x86_64.rpm
python-meld3-0.6.10-1.noarch.rpm
python-setuptools-0.6.10-3.el6.noarch.rpm
python-supervisor-3.0-1.noarch.rpm
ttmkfdir-3.0.9-32.1.el6.x86_64.rpm
tzdata-java-2017a-1.el6.noarch.rpm
xorg-x11-font-utils-7.2-11.el6.x86_64.rpm
xorg-x11-fonts-Type1-7.2-11.el6.noarch.rpm

CentOS/Redhat 7

alsa-lib-1.1.1-1.el7.x86_64.rpm
bzip2-1.0.6-13.el7.x86_64.rpm
chkconfig-1.7.2-1.el7.x86_64.rpm
copy-jdk-configs-1.2-1.el7.noarch.rpm
fontconfig-2.10.95-10.el7.x86_64.rpm
fontpackages-filesystem-1.44-8.el7.noarch.rpm
giflib-4.1.6-9.el7.x86_64.rpm
java-1.8.0-openjdk-1.8.0.121-0.b13.el7_3.x86_64.rpm
java-1.8.0-openjdk-devel-1.8.0.121-0.b13.el7_3.x86_64.rpm
java-1.8.0-openjdk-headless-1.8.0.121-0.b13.el7_3.x86_64.rpm
javapackages-tools-3.4.1-11.el7.noarch.rpm
libICE-1.0.9-2.el7.x86_64.rpm
libSM-1.2.2-2.el7.x86_64.rpm
libX11-1.6.3-3.el7.x86_64.rpm
libX11-common-1.6.3-3.el7.noarch.rpm
libXau-1.0.8-2.1.el7.x86_64.rpm
libXcomposite-0.4.4-4.1.el7.x86_64.rpm
libXext-1.3.3-3.el7.x86_64.rpm
libXfont-1.5.1-2.el7.x86_64.rpm
libXi-1.7.4-2.el7.x86_64.rpm
libXrender-0.9.8-2.1.el7.x86_64.rpm
libXtst-1.2.2-2.1.el7.x86_64.rpm
libfontenc-1.1.2-3.el7.x86_64.rpm
libjpeg-turbo-1.2.90-5.el7.x86_64.rpm
libpng-1.5.13-7.el7_2.x86_64.rpm
libxcb-1.11-4.el7.x86_64.rpm
lksctp-tools-1.0.17-2.el7.x86_64.rpm
nginx-1.6.2-1.el7.ngx.x86_64.rpm
nodejs-10.13.0-1nodesource.el7.centos.x86_64.rpm
nspr-4.11.0-1.el7_2.x86_64.rpm
nss-3.21.3-2.el7_3.x86_64.rpm
nss-softokn-3.16.2.3-14.4.el7.x86_64.rpm
nss-softokn-freebl-3.16.2.3-14.4.el7.x86_64.rpm
nss-sysinit-3.21.3-2.el7_3.x86_64.rpm
nss-tools-3.21.3-2.el7_3.x86_64.rpm
nss-util-3.21.3-1.1.el7_3.x86_64.rpm
openldap-clients-2.4.40-13.el7.x86_64
openssl x86_64 1:1.0.2k-12.el7
python-javapackages-3.4.1-11.el7.noarch.rpm
python-meld3-0.6.10-1.el7.x86_64.rpm
python-setuptools-0.9.8-4.el7.noarch.rpm
supervisor-3.1.3-3.el7.noarch.rpm
ttmkfdir-3.0.9-42.el7.x86_64.rpm
tzdata-java-2016j-1.el7.noarch.rpm
xorg-x11-font-utils-7.5-20.el7.x86_64.rpm
xorg-x11-fonts-Type1-7.5-9.el7.noarch.rpm

Ubuntu 14.04 / Ubuntu 16.04

Please contact *Trifacta Support*.

Desktop Requirements

Contents:

- *Browser Requirements*
 - *Google Chrome Requirements*
 - *Desktop Requirements*
 - *General Requirements*
 - *Wrangler Enterprise desktop application Requirements*
-

Browser Requirements

These requirements apply to Trifacta® Wrangler Enterprise, which interacts with the platform through the browser.

Access to the platform requires Google Chrome. For more information, see <https://www.google.com/chrome/>.

NOTE: Parts of the application may become hidden or distorted unless zoom level is set to 100%.

NOTE: In some cases, ad blocking extensions in your Google Chrome browser, such as Adblock, can interfere with loading Trifacta datasets. You may need to disable the extension, particularly if you are loading marketing data.

NOTE: Multiple browser tabs or windows open to different versions of the product is not supported.

NOTE: If you are using the Wrangler Enterprise desktop application, an installed instance of Chrome is not required. Additional requirements are listed below.

Google Chrome Requirements

Trifacta Wrangler Enterprise requires the use of Google-supported client extensions. Supported desktop Google Chrome clients:

WebAssembly client extension

No other configuration is required.

Tip: WebAssembly is the default client deployed by the platform.

Limitations:

In this release, the following limitations apply to use of WebAssembly:

- The current implementation of WebAssembly in this release is single-threaded, and performance may be impacted.
 - Google has not yet implemented multi-threaded WebAssembly.

- When multi-threading is available, the Trifacta Photon client will feature multi-threading.
- Progress bars are not displayed for actions in the Transformer page. This is a known issue.

PNaCl client extension

Additional installation and enablement is required on each desktop. See below.

Support for PNaCl desktop client is likely to be deprecated in a future release. Please upgrade your Google Chrome browser to 68+.

The component is downloaded from Google and updated after Chrome's installation. Therefore, an internet connection is required for its initial download. Notes:

- The component also must not be blocked by any enterprise policies. To check yours, navigate to *chrome://policy*.
- For more information on how to enable this plugin, see *Configure Desktops*.
- If you are using Incognito mode to access the application, you are forced to refresh the client each time you open the Transformer page. Avoid Incognito mode.
- For more information, see *Configure Photon Client*.

Browser version

Version: Google Chrome v.72, v.73, and any stable of version that is released prior to the next release of Trifacta Wrangler Enterprise.

NOTE: To access Trifacta Wrangler Enterprise you must use a supported desktop version of the Google Chrome browser, unless you are using Wrangler Enterprise desktop application.

NOTE: Mobile browsers and Google Chromebook are not supported.

Ports

By default, the web client uses port 3005.

For more information on required client ports, see *System Ports*.

Desktop Requirements

The following requirements apply to your local system.

General Requirements

- Intel Pentium 4 or AMD Opteron processor or newer (SSE2 or newer is required)
- 4 GB RAM

Tip: At least 8 GB RAM is recommended.

- 2 GB hard disk space
- 1280 x 720 screen resolution and above
- Internet connection (DSL or better)

NOTE: Trifacta® Wrangler Enterprise does not support connection through non-transparent or unauthenticated proxies. If you receive "Remote server timed out" error messages, you may need to re-connect through a network without a proxy.

Wrangler Enterprise desktop application Requirements

The Wrangler Enterprise desktop application can be used locally to interact with Trifacta Wrangler Enterprise and can be installed in your local environment. Please verify that the following requirements are met.

System requirements

In addition to the general desktop requirements, the following requirements apply to the Wrangler Enterprise desktop application:

- 8 GB RAM minimum

Windows requirements

- Windows 7 (Service Pack 1), 8, or 10. 64-bit versions.

NOTE: The Wrangler Enterprise desktop application requires a 64-bit version of Microsoft Windows.

- Visual C++ for Visual Studio 2015 (`vc_redist.x86.exe`). To download:
<https://www.microsoft.com/en-us/download/details.aspx?id=48145>.

Windows execution

When the installation is completed, most users should be able to launch the local application without issues. If you are experiencing issues launching the application, please verify that all DLL and EXE files in the following directory are executable:

Tip: This requirement typically applies to more secure environments. Most desktop users should not have to modify permissions.

```
C:\Users\\AppData\Local\Trifacta\Trifacta Wrangler Enterprise\
```

Supported File Formats

Contents:

- *Native Input File Formats*
 - *Native Output File Formats*
 - *Compression Algorithms*
 - *Read Native File Formats*
 - *Write Native File Formats*
 - *Additional Configuration for File Format Support*
 - *Publication of some formats requires execute permissions*
-

This section contains information on the file formats and compression schemes that are supported for input to and output of Trifacta® Wrangler Enterprise.

NOTE: To work with formats that are proprietary to a desktop application, such as Microsoft Excel, you do not need the supporting application installed on your desktop.

Native Input File Formats

Trifacta® Wrangler Enterprise can read and import directly these file formats:

- Excel (XLS/XLSX)

Tip: You may import multiple worksheets from a single workbook at one time. See *Import Excel Data*.

- CSV
- JSON, including nested

NOTE: Trifacta Wrangler Enterprise requires that JSON files be submitted with one valid JSON object per line. Consistently malformed JSON objects or objects that overlap linebreaks might cause import to fail. See *Initial Parsing Steps*.

- Plain Text
- LOG
- TSV
- Parquet

NOTE: When working with datasets sourced from Parquet files, lineage information and the `$sourcerownumber` reference are not supported.

-

XML

NOTE: XML files can be ingested as unstructured text. XML support is not enabled by default. For more information, please contact *Trifacta Customer Success Services*.

- Avro

For more information on data is handled initially, see *Initial Parsing Steps*.

Native Output File Formats

Trifacta Wrangler Enterprise can write to these file formats:

- CSV
- JSON

- Tableau (TDE)

NOTE: Publication of results in TDE format may require additional configuration. See below.

- Avro

NOTE: The Trifacta Photon and Spark running environments apply Snappy compression to this format.

- Parquet

NOTE: The Trifacta Photon and Spark running environments apply Snappy compression to this format.

Compression Algorithms

NOTE: Importing a compressed file with a high compression ratio can overload the available memory for the application. In such cases, you can decompress the file before uploading. If decompression fails, you should contact your administrator about increasing the Java Heap Size memory.

NOTE: Publication of results in Snappy format may require additional configuration. See below.

NOTE: GZIP files on Hadoop are not split across multiple nodes. As a result, jobs can crash when processing it through a single Hadoop task. This is a known issue with GZIP on Hadoop.

Where possible, limit the size of your GZIP files to 100 MB or less, or use BZIP2 as an alternative compression method. As a workaround, you can try to run the job on the unzipped file. You may also disable profiling for the job. See *Run Job Page*.

Read Native File Formats

	GZIP	BZIP	Snappy
CSV	Supported	Supported	Supported
JSON	Supported	Supported	Supported
Avro			Supported
Hive			Supported

Write Native File Formats

	GZIP	BZIP	Snappy
CSV	Supported	Supported	Supported
JSON	Supported	Supported	Supported
Avro			Supported; always on

Hive		Supported; always on
------	--	----------------------

Additional Configuration for File Format Support

Publication of some formats requires execute permissions

When job results are generated and published in the following formats, the Trifacta platform includes a JAR, from which is extracted a binary executable into a temporary directory. From this directory, the binary is then executed to generate the results in the proper format. By default, this directory is set to `/tmp` on the Trifacta node.

In many environments, execute permissions are disabled on `/tmp` for security reasons. Use the steps below to specify the temporary directory where this binary can be moved and executed.

Steps:

1. Login to the application as an administrator.
2. From the menu, select **Settings menu > Settings > Admin Settings**.
3. For each of the following file formats, locate the listed parameter, where the related binary code can be executed:

File Format	Parameter	Setting to Add
Snappy	"data-service.jvmOptions"	-Dorg.xerial.snappy.tmpdir=<some executable directory>
TDE	"batch-job-runner.jvmOptions"	-Djna.tmpdir=<some executable directory>

4. Save your changes and restart the platform.
5. Run a job configured for direct publication of the modified file format.

Required Users and Groups

Contents:

- *Installation node*
 - *Install*
 - *Running Services*
 - *Active Directory/LDAP*
- *Databases*
 - *Main database*
 - *Jobs database*
- *Hadoop*
 - *Hadoop User*
 - *Kerberos*
 - *Hive*
- *HDInsight*

- *Cluster*
-

The following users may be required for installation of the Trifacta® platform and integration with other components in the environment. In some cases, you must also designate a group in which the user or users must belong.

NOTE: Except as noted, you may substitute your own usernames for the default usernames. These substitutions are identified in the documentation references.

In this sections below, you can review the user requirements for various aspects of platform installation and integration.

Legend:

- **Required configuration:** If Yes, then the configuration and the relevant user are required for all installations of the platform.
- **Default user:** Default or expected username for the user.
- **Documentation reference:** How the user is referenced in the documentation.
- **Documentation link:** For more information on configuring for the listed component, please visit the listed link, where application of these values is described in greater detail.

Installation node

Install

NOTE: The software must be installed on the node using the `root` account.

- **Documentation link:** *Install Enterprise on CentOS and RHEL*

Running Services

After installation, you can run the platform as the `trifacta` user.

- **Documentation link:** *Start and Stop the Platform*

Active Directory/LDAP

When enabling Single Sign-On, you must specify an Active Directory user to serve as the admin for provisioning users within the Trifacta platform.

- **Required configuration:** No
- **Defaults:**
 - User: `trifacta`
 - Group: `trifactausers`
- **Documentation reference:**
 - User: `[ldap.user]`
 - Group: `[ldap.group]`
- **Documentation link:** *Configure SSO for AD-LDAP*

Databases

The Trifacta platform installs and maintains two databases.

Main database

The Main database is used for managing Trifacta metadata.

- **Required configuration:** Yes
- **Default user:** `trifacta`
- **Documentation reference:** `[db.main.user]`
- **Documentation link:** *Install Databases*

Jobs database

The Jobs database is used for tracking batch execution jobs initiated by the platform.

- **Required configuration:** Yes
- **Default user:** `trifactaactiviti`
- **Documentation reference:** `[db.jobs.user]`
- **Documentation link:** *Install Databases*

Hadoop

Hadoop User

When the platform interacts with the Hadoop cluster, all actions are brokered through the use of a single Hadoop user account.

NOTE: This user account is specified and used in multiple configurations for integration with the Hadoop cluster.

- **Required configuration:** Yes
- **Defaults:**
 - User: `trifacta`
 - Group: `trifactausers`
- **Documentation references:**
 - User: `[hadoop.user]`
 - Group: `[hadoop.group]`
- **Documentation link:** *Configure for Hadoop*

Kerberos

If Kerberos is enabled on your cluster, you must specify the principal of the Hadoop user for the Trifacta platform. Depending on the other components available in the cluster, you may need to specify other Kerberos principals.

- **Required configuration:** No
- **Default user:** `trifacta`
- **Documentation reference:** `[hadoop.user.principal]`
- **Documentation links:**
 - Kerberos: *Configure for Kerberos Integration*
 - Secure impersonation: *Configure for Secure Impersonation*

Hive

You must specify a user that Hive uses to connect to HDFS.

- **Required configuration:** No
- **Defaults:**
 - User: `hive`
 - Group: `trifactausers`
- **Documentation references:**
 - User: `[hive.user]`
 - Group: `[hive.group]`
- **Documentation link:** *Configure for Hive*

HDInsight

Cluster

When integrating with HDInsight, you must specify a user for the platform to use with its connections to HDI.

- **Required configuration:** No
- **Defaults:**
 - User: `trifacta`
 - Group: `trifactausers`
- **Documentation references:**
 - User: `[hdi.user]`
 - Group: `[hdi.group]`
- **Documentation link:** *Configure for HDInsight*

Prepare Hadoop for Integration with the Platform

Contents:

- *Create Trifacta user account on Hadoop cluster*
- *HDFS directories*
- *Kerberos authentication*
- *Hadoop component configuration*
 - *Acquire cluster configuration files*
 - *YARN configuration overview*
 - *Spark configuration overview*
 - *Recommendations*

Before you deploy the Trifacta® software, you should complete the following configuration steps within your Hadoop environment.

- For a technical overview of how the Trifacta platform interacts with Hadoop, see *Platform Interactions with Hadoop*.

NOTE: The Trifacta platform requires access to a set of Hadoop components. See *System Requirements*.

Create Trifacta user account on Hadoop cluster

The Trifacta platform interacts with Hadoop through a single system user account. A user for the platform must be added to the cluster.

NOTE: In a cluster without Kerberos or SSO user management, the `[hadoop.user (default=trifacta)]` user must be created on each node of the cluster.

If LDAP is enabled, the `[hadoop.user]` user should be created in the same realm as the cluster.

If Kerberos is enabled, the `[hadoop.user]` user must exist on every node where jobs run.

For POSIX-compliant Hadoop environments, the user IDs of the Trifacta user accessing the cluster and the Hadoop user must match exactly.

UserID:

If possible, please create the user ID as: `trifacta`

This user should belong to the group: `trifactausers`

User requirements:

- Access to HDFS
- Permission to run YARN jobs on the cluster.

Verify that the following HDFS paths have been created and that their permissions enable access to the Trifacta user account:

NOTE: Depending on your Hadoop distribution, you may need to modify the following commands to use the Hadoop client installed on the Trifacta node.

Below, change the values for `trifacta` to match the `[hadoop.user]` user for your environment:

```
hdfs dfs -mkdir /trifacta
hdfs dfs -chown trifacta /trifacta
hdfs dfs -mkdir -p /user/trifacta
hdfs dfs -chown trifacta /user/trifacta
```

HDFS directories

The following directories must be available to the `[hadoop.user]` on HDFS. Below, you can review the minimum permissions set for basic and impersonated authentication for each default directory. Secure impersonation is described later.

NOTE: Except for the `dictionaries` directory, which is used to hold smaller reference files, each of these directories should be configured to permit storage of a user's largest datasets.

Directory	Minimum required permissions	Secure impersonation permissions
-----------	------------------------------	----------------------------------

/trifacta/uploads	700	770 Set this to 730 to prevent users from browsing this directory.
/trifacta/queryResults	700	770
/trifacta/dictionaries	700	770
/trifacta/tempfiles	770	770

You can use the following commands to configure permissions on these directories. Following permissions scheme reflects the secure impersonation permissions in the above table:

```

$ hdfs dfs -mkdir -p /trifacta/uploads
$ hdfs dfs -mkdir -p /trifacta/queryResults
$ hdfs dfs -mkdir -p /trifacta/dictionaries
$ hdfs dfs -mkdir -p /trifacta/tempfiles
$ hdfs dfs -chown -R trifacta:trifacta /trifacta
$ hdfs dfs -chmod -R 770 /trifacta
$ hdfs dfs -chmod -R 730 /trifacta/uploads

```

If these standard locations cannot be used, you can configure the HDFS paths. You can apply this change through the *Admin Settings Page* (recommended) or `trifacta-conf.json`. For more information, see *Platform Configuration Methods*.

```

"hdfs.pathsConfig.fileUpload": "/trifacta/uploads",
"hdfs.pathsConfig.batchResults": "/trifacta/queryResults",
"hdfs.pathsConfig.dictionaries": "/trifacta/dictionaries",

```

Kerberos authentication

The Trifacta platform supports Kerberos authentication on Hadoop.

NOTE: If Kerberos is enabled for the Hadoop cluster, the keytab file must be made accessible to the Trifacta platform. See *Configure for Kerberos Integration*.

Hadoop component configuration

Acquire cluster configuration files

The Hadoop cluster configuration files must be made available to the Trifacta platform. You can either copy the files over from the cluster or create a local symlink to them.

For more information, see *Configure for Hadoop*.

YARN configuration overview

This section provides an overview of configuration recommendations to be applied to the Hadoop cluster from the Trifacta platform.

NOTE: The recommendations in this section are optimized for use with the Trifacta platform. These may or may not conform to requirements for other applications using the Hadoop cluster. Trifacta assumes no responsibility for the configuration of the cluster.

YARN manages cluster resources (CPU and memory) by running all processes within allocated containers. Containers restrict the resources available to its process(es). Processes are monitored and killed if they overrun the container allocation.

- Multiple containers can run on a cluster node (if available resources permit).
- A job can request and use multiple containers across the cluster.
- Container requests specify virtual CPU (cores) and memory (in MB).

YARN configuration specifies:

- **Per Cluster Node:** Available virtual CPUs and memory per cluster node
- **Per Container:** virtual CPUs and memory for each container

The following parameters are available in `yarn-site.xml`:

Parameter	Type	Description
<code>yarn.nodemanager.resource.memory-mb</code>	Per Cluster Node	Amount of physical memory, in MB, that can be allocated for containers
<code>yarn.nodemanager.resource.cpu-vcores</code>	Per Cluster Node	Number of CPU cores that can be allocated for containers
<code>yarn.scheduler.minimum-allocation-mb</code>	Per Container	Minimum container memory, in MBs; requests lower than this will be increased to this value
<code>yarn.scheduler.maximum-allocation-mb</code>	Per Container	Maximum container memory, in MBs; requests higher than this will be capped to this value
<code>yarn.scheduler.increment-allocation-mb</code>	Per Container	Granularity of container memory requests
<code>yarn.scheduler.minimum-allocation-vcores</code>	Per Container	Minimum allocation virtual CPU cores per container; requests lower than will be increased to this value.
<code>yarn.scheduler.maximum-allocation-vcores</code>	Per Container	Maximum allocation virtual CPU cores per container; requests higher than this will be capped to this value
<code>yarn.scheduler.increment-allocation-vcores</code>	Per Container	Granularity of container virtual CPU requests

Spark configuration overview

Spark processes run multiple executors per job. Each executor must run within a YARN container. Therefore, resource requests must fit within YARN's container limits.

Like YARN containers, multiple executors can run on a single node. More executors provide additional computational power and decreased runtime.

Spark's dynamic allocation adjusts the number of executors to launch based on the following:

- job size
- job complexity
- available resources

You can apply this change through the *Admin Settings Page* (recommended) or `trifacta-conf.json`. For more information, see *Platform Configuration Methods*.

The per-executor resource request sizes can be specified by setting the following properties in the `spark.props` section :

NOTE: In `trifacta-conf.json`, all values in the `spark.props` section must be quoted values.

Parameter	Description
<code>spark.executor.memory</code>	Amount of memory to use per executor process (in a specified unit)
<code>spark.executor.cores</code>	Number of cores to use on each executor - limit to 5 cores per executor for best performance

A single special process, the application driver, also runs in a container. Its resources are specified in the `spark.props` section:

Parameter	Description
<code>spark.driver.memory</code>	Amount of memory to use for the driver process (in a specified unit)
<code>spark.driver.cores</code>	Number of cores to use for the driver process

Recommendations

The following configuration settings can be applied through Trifacta platform configuration based on the number of nodes in the Hadoop cluster.

NOTE: These recommendations should be modified based on the technical capabilities of your network, the nodes in the cluster, and other applications using the cluster.

	1	2	4	10	16
Available memory (GB)	16	32	64	160	256
Available vCPUs	4	8	16	40	64
<code>yarn.nodemanager.resource.memory-mb</code>	12288	24576	57344	147456	245760
<code>yarn.nodemanager.resource.cpu-vcores</code>	3	6	13	32	52
<code>yarn.scheduler.minimum-allocation-mb</code>	1024	1024	1024	1024	1024
<code>yarn.scheduler.maximum-allocation-mb</code>	12288	24576	57344	147456	245760
<code>yarn.scheduler.increment-allocation-mb</code>	512	512	512	512	512
<code>yarn.scheduler.minimum-allocation-vcores</code>	1	1	1	1	1
<code>yarn.scheduler.maximum-allocation-vcores</code>	3	6	13	32	52
<code>yarn.scheduler.increment-allocation-vcores</code>	1	1	1	1	1
<code>spark.executor.memory</code>	6GB	6GB	16GB	20GB	20GB

spark.executor.cores	2	2	4	5	5
spark.driver.memory	4GB	4GB	4GB	4GB	4GB
spark.driver.cores	1	1	1	1	1

The specified configuration allows, maximally, the following Spark configuration per node:

CoresxNode	Configuration Options
1x1	(1 driver + 1 executor) or 1 executor
2x1	(1 driver + 2 executor) or 3 executors
4x1	(1 driver + 3 executors) or 3 executors
10x1	(1 driver + 6 executors) or 6 executors
16x1	(1 driver + 10 executors) or 10 executors



Copyright © 2019 - Trifacta, Inc.
All rights reserved.