

SUFFIX Function

Finds the suffix value after the domain from a valid URL. Input values must be of URL or String type.

This function is part of a set of functions for processing URL data.

- See *DOMAIN Function*.
- See *SUBDOMAIN Function*.
- For more information, see *Structure of a URL*.

Basic Usage

URL literal examples:

```
suffix('http://www.example.com')
```

Output: Returns the value `com`.

```
suffix('http://www.examp.l.e.com')
```

Output: Returns the value `com`.

Column reference example:

```
suffix(myURLs)
```

Output: Returns the suffix values extracted from the `myURLs` column.

Syntax

```
suffix(column_url)
```

Argument	Required?	Data Type	Description
column_url	Y	string	Name of column or String or URL literal containing the suffix value to extract

For more information on syntax standards, see *Language Documentation Syntax Notes*.

column_url

Name of the column or URL or String literal whose values are used to extract the suffix value.

- Missing input values generate missing results.
- Multiple columns and wildcards are not supported.

Usage Notes:

Required?	Data Type	Example Value
Yes	String literal or column reference (URL)	http://www.example.com

Examples

Example - Domain, Subdomain, Host, and Suffix functions

This examples illustrates how you can extract component parts of a URL using the following functions:

- DOMAIN - extracts the domain value from a URL. See *DOMAIN Function*.
- SUBDOMAIN - extracts the first group after the protocol identifier and before the domain value. See *SUBDOMAIN Function*.
- HOST - returns the complete value of the host from an URL. See *HOST Function*.
- SUFFIX - extracts the suffix of a URL. See *SUFFIX Function*.
- URLPARAMS - extracts the query parameters and values from a URL. See *URLPARAMS Function*.
- FILTEROBJECT - filters an Object value to show only the elements for a specified key. See *FILTEROBJECT Function*.

Source:

Your dataset includes the following values for URLs:

URL
www.example.com
example.com/support
http://www.example.com/products/
http://1.2.3.4
https://www.example.com/free-download
https://www.example.com/about-us/careers
www.app.example.com
www.some.app.example.com
some.app.example.com
some.example.com
example.com
http://www.example.com?q1=broken%20record
http://www.example.com?query=khakis&app=pants
http://www.example.com?q1=broken%20record&q2=broken%20tape&q3=broken%20wrist

Transformation:

When the above data is imported into the application, the column is recognized as a URL. All values are registered as valid, even the IPv4 address.

To extract the domain and subdomain values:

Transformation Name	New formula
Parameter: Formula type	Single row formula

Parameter: Formula	DOMAIN(URL)
Parameter: New column name	'domain_URL'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	SUBDOMAIN(URL)
Parameter: New column name	'subdomain_URL'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	HOST(URL)
Parameter: New column name	'host_URL'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	SUFFIX(URL)
Parameter: New column name	'suffix_URL'

You can use the Trifacta® pattern in the following transformation to extract protocol identifiers, if present, into a new column:

Transformation Name	Extract text or pattern
Parameter: Column to extract from	URL
Parameter: Option	Custom text or pattern
Parameter: Text to extract	`{start}%*://`

To clean this up, you might want to rename the column to `protocol_URL`.

To extract the path values, you can use the following regular expression:

NOTE: Regular expressions are considered a developer-level method for pattern matching. Please use them with caution. See *Text Matching*.

Transformation Name	Extract text or pattern
Parameter: Column to extract from	URL
Parameter: Option	Custom text or pattern
Parameter: Text to extract	/[[^] *:\//]\./.*\$/

The above transformation grabs a little too much of the URL. If you rename the column to `path_URL`, you can use the following regular expression to clean it up:

Transformation Name	Extract text or pattern
Parameter: Column to extract from	URL

Parameter: Option	Custom text or pattern
Parameter: Text to extract	/[!^\s/].*\$/

Delete the `path_URL` column and rename the `path_URL1` column to the deleted one. Then:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	URLPARAMS(URL)
Parameter: New column name	'urlParams'

If you wanted to just see the values for the `q1` parameter, you could add the following:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	FILTEROBJECT(urlParams, 'q1')
Parameter: New column name	'urlParam_q1'

Results:

For display purposes, the results table has been broken down into separate sets of columns.

Column set 1:

URL	host_URL	path_URL
www.example.com	www.example.com	
example.com/support	example.com	/support
http://www.example.com/products/	www.example.com	/products/
http://1.2.3.4	1.2.3.4	
https://www.example.com/free-download	www.example.com	/free-download
https://www.example.com/about-us/careers	www.example.com	/about-us/careers
www.app.example.com	www.app.example.com	
www.some.app.example.com	www.some.app.example.com	
some.app.example.com	some.app.example.com	
some.example.com	some.example.com	
example.com	example.com	
http://www.example.com?q1=broken%20record	www.example.com	
http://www.example.com?query=khakis&app=pants	www.example.com	
http://www.example.com?q1=broken%20record&q2=broken%20tape&q3=broken%20wrist	www.example.com	

Column set 2:

URL	protocol_URL	subdomain_URL	domain_URL	suffix_URL
www.example.com		www	example	com
example.com/support			example	com
http://www.example.com/products/	http://	www	example	com
http://1.2.3.4	http://			
https://www.example.com/free-download	https://	www	example	com
https://www.example.com/about-us/careers	https://	www	example	com
www.app.example.com		www.app	example	com
www.some.app.example.com		www.some.app	example	com
some.app.example.com		some.app	example	com
some.example.com		some	example	com
example.com			example	com
http://www.example.com?q1=broken%20record	http://	www	example	com
http://www.example.com?query=khakis&app=pants	http://	www	example	com
http://www.example.com?q1=broken%20record&q2=broken%20tape&q3=broken%20wrist	http://	www	example	com

Column set 3:

URL	uriParams	uriParam_q1
www.example.com		
example.com/support		
http://www.example.com/products/		
http://1.2.3.4		
https://www.example.com/free-download		
https://www.example.com/about-us/careers		
www.app.example.com		
www.some.app.example.com		
some.app.example.com		
some.example.com		
example.com		
http://www.example.com?q1=broken%20record	{"q1":"broken record"}	{"q1":"broken record"}
http://www.example.com?query=khakis&app=pants	{"query":"khakis","app":"pants"}	

http://www.example.com?q1=broken%
20record&q2=broken%
20tape&q3=broken%20wrist

```
{"q1":"broken record", "q2":"broken tape",  
"q3":"broken wrist"}
```

```
{"q1":"broken record"}
```