

AVERAGE Function

Computes the average (mean) from all row values in a column. Input column can be of Integer or Decimal.

- If a row contains a missing or null value, it is not factored into the calculation. If the entire column contains no values, the function returns a null value.
- When used in a `pivot` transform, the function is computed for each instance of the value specified in the `group` parameter. See *Pivot Transform*.

For a version of this function computed over a rolling window of rows, see *ROLLINGAVERAGE Function*.

Basic Usage

```
average(myRating)
```

Output: Returns the average of the values in the `myRating` column.

Syntax

```
average(function_col_ref) [group:group_col_ref] [limit:limit_count]
```

Argument	Required?	Data Type	Description
function_col_ref	Y	string	Name of column to which to apply the function

For more information on the `group` and `limit` parameters, see *Pivot Transform*.

For more information on syntax standards, see *Language Documentation Syntax Notes*.

function_col_ref

Name of the column the values of which you want to calculate the average. Column must contain Integer or Decimal values.

- Literal values are not supported as inputs.
- Multiple columns and wildcards are not supported.

Usage Notes:

Required?	Data Type	Example Value
Yes	String (column reference)	myValues

Examples

Example - Statistics on Test Scores

This example illustrates how you can apply statistical functions to your dataset. Calculations include average (mean), max, min, standard deviation, and variance.

Source:

Students took a test and recorded the following scores. You want to perform some statistical analysis on them:

Student	Score
Anna	84
Ben	71
Caleb	76
Danielle	87
Evan	85
Faith	92
Gabe	85
Hannah	99
Ian	73
Jane	68

Transformation:

You can use the following transforms to calculate the average (mean), minimum, and maximum scores:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	AVERAGE(Score)
Parameter: New column name	'avgScore'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	MIN(Score)
Parameter: New column name	'minScore'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	MAX(Score)
Parameter: New column name	'maxScore'

To apply statistical functions to your data, you can use the VAR and STDEV functions, which can be used as the basis for other statistical calculations.

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	VAR(Score)

Transformation Name	New formula
----------------------------	-------------

Parameter: Formula type	Single row formula
Parameter: Formula	STDEV(Score)

For each score, you can now calculate the variation of each one from the average, using the following:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	$((\text{Score} - \text{avg_Score}) / \text{stdev_Score})$
Parameter: New column name	'stDevs'

Now, you want to apply grades based on a formula:

Grade	standard deviations from avg (stDevs)
A	stDevs > 1
B	stDevs > 0.5
C	-1 <= stDevs <= 0.5
D	stDevs < -1
F	stDevs < -2

You can build the following transform using the IF function to calculate grades.

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	IF((stDevs > 1), 'A', IF((stDevs < -2), 'F', IF((stDevs < -1), 'D', IF((stDevs > 0.5), 'B', 'C'))))

For more information, see *IF Function*.

To clean up the content, you might want to apply some formatting to the score columns. The following reformats the stdev_Score and stDevs columns to display two decimal places:

Transformation Name	Edit column with formula
Parameter: Columns	stdev_Score
Parameter: Formula	NUMFORMAT(stdev_Score, '##.00')

Transformation Name	Edit column with formula
Parameter: Columns	stDevs
Parameter: Formula	NUMFORMAT(stDevs, '##.00')

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	MODE(Score)
Parameter: New column name	'modeScore'

Results:

Student	Score	modeScore	avgScore	minScore	maxScore	var_Score	stdev_Score	stDevs	Grade
Anna	84	85	82	68	99	87.00000000000001	9.33	0.21	C
Ben	71	85	82	68	99	87.00000000000001	9.33	-1.18	D
Caleb	76	85	82	68	99	87.00000000000001	9.33	-0.64	C
Danielle	87	85	82	68	99	87.00000000000001	9.33	0.54	B
Evan	85	85	82	68	99	87.00000000000001	9.33	0.32	C
Faith	92	85	82	68	99	87.00000000000001	9.33	1.07	A
Gabe	85	85	82	68	99	87.00000000000001	9.33	0.32	C
Hannah	99	85	82	68	99	87.00000000000001	9.33	1.82	A
Ian	73	85	82	68	99	87.00000000000001	9.33	-0.96	C
Jane	68	85	82	68	99	87.00000000000001	9.33	-1.50	D