

# EXAMPLE - Case Functions

## Source:

In the following example, you can see a number of input values in the leftmost column. The output columns are blank.

input	uppercase	lowercase	propercase
AbCdEfGh IjKIMnO			
go West, young man!			
Oh, *(*\$%(&! That HURT!			
A11 w0rk and n0 0play makes Jack a dull boy.			

## Transform:

To generate uppercase, lowercase, and propercase values in the output columns, use the following transforms:

```
set col:uppercase value:UPPER(input)
```

```
set col:lowercase value:LOWER(input)
```

```
set col:propercase value:PROPER(input)
```

## Results:

input	uppercase	lowercase	propercase
AbCdEfGh IjKIMnO	ABCDEFGH IJKLMNO	abcdefgh ijklmno	Abcdefgh Ijklmno
go West, young man!	GO WEST, YOUNG MAN!	go west, young man!	Go West, Young Man!
Oh, *(*\$%(&! That HURT!	OH, *(*\$%(&! THAT HURT!	oh, *(*\$%(&! that hurt!	Oh, *(*\$%(&! That Hurt!
A11 w0rk and n0 0play makes Jack a dull boy.	A11 W0RK AND N0 0PLAY MAKES JACK A DULL BOY.	a11 w0rk and n0 0play makes jack a dull boy.	A11 W0rk And N0 0play Makes Jack A Dull Boy.