

API Deployments Value Import Rules Patch v3



As of Release 6.4, the v3 APIs are End of Life (EOL). Before using this release or a later one, you should migrate to using the latest available API version. For more information, see *API Version Support Matrix*. Latest version of this endpoint: *API Deployments Value Import Rules Patch v4*.

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Create a list of value-based import rules for the specified deployment. Delete any previous rules applied to the same values.

NOTE: Import rules must be applied to individual deployments.

The generated rules apply to all flows that are imported into the Production instance after they have been created.

NOTE: Deployments pertain to Production instances of the Trifacta® platform. For more information, see *Overview of Deployment Manager*.

The response contains any previously created rules that have been deleted as a result of this change.

You can also make replacements in the import package based on object references. See *API Deployments Object Import Rules Patch v3*.

Version: v3

Required Permissions

NOTE: Each request to the Trifacta® platform must include authentication credentials. See *API Authentication*.

Request

Request Type: PATCH

Endpoint:

```
/v3/deployments/<id>/valueImportRules
```

where:

| Parameter | Description |
|-----------|--|
| <id> | Internal identifier for the deployment |

Request URI - Example:

```
/v3/deployments/4/valueImportRules
```

Request Body Example: Single value replacement

The following JSON array describes a single replacement rule for the S3 bucket name. In this case, the `wrangle-dev` bucket name has been replaced by the `wrangle-prod` bucket name, which means data is pulled in the Production deployment from the appropriate S3 bucket.

NOTE: The executing user of any job must have access to any data source that is remapped in the new instance.

```
[{"type": "s3Bucket", "on": "wrangle-dev", "with": "wrangle-prod"}]
```

Request Body Example: Multiple value replacements

The following JSON array describes two replacements for the `fileLocation` values. In this case, rules are applied in succession.

NOTE: Rules are applied in the listed order. If you are applying multiple rules to the same object in the import package, the second rule must reference the expected changes applied by the first rule.

```
[{"type": "fileLocation", "on": "klamath", "with": "klondike"}, {"type": "fileLocation", "on": "/\\dev\\/", "with": "/prod/"}
```

In the above:

- The first rule replaces the string `klamath` in the path to the source with the following value: `klondike`.
- The second rule performs a regular expression match on the string `/dev/`. Since the match is described using the regular expression syntax, the backslashes must be escaped. The replacement value is the following literal: `/prod/`.

You can specify matching values using the following types of matches:

| Match Type | Example Syntax |
|--------------------|---|
| string literal | <code>{"on": "d75255f0-a245-11e7-8618-adc1dbb4bed0" }</code> |
| regular expression | <code>{"on": "[0-9a-zA-Z]{8}-a245-11e7-8618-adc1dbb4bed0/" }</code> |

NOTE: Use of Trifacta patterns is not supported.

For more information on patterns, see [Text Matching](#).

Response

Response Status Code - Success: 200 - OK

The response body contains any previously created rules that have been deleted as a result of this update.

Response Body Example: All new rule, no deletions

If the update does not overwrite any previous rules, then no rules are deleted. So, the response looks like the following:

```
{
  "deleted": []
}
```

Response Body Example: Replace file location, delete previous rule

If you submit the request again, the response contains the rule definition of the previous update, which has been deleted.

```
{
  "deleted": [
    {
      "on": "wrangle-dev",
      "id": 1,
      "type": "s3Bucket",
      "with": "wrangle-prod",
      "createdBy": 3,
      "updatedBy": 3,
      "createdAt": "2017-11-07T02:16:57.743Z",
      "updatedAt": "2017-11-07T02:16:57.743Z",
      "deploymentId": 1
    }
  ]
}
```

Reference

| Property | Description |
|--------------|--|
| on | The specified literal or pattern to match. |
| id | Internal identifier for the value import rule |
| type | The type of value import rule: <ul style="list-style-type: none">fileLocation - the location of a specified file.s3Bucket - location of the S3 bucket to modify |
| with | The replacement value or pattern |
| deploymentId | Internal identifier for the deployment to which to apply the import rule. |