

API ImportedDatasets Post AddToFlow v3

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Add the specified imported dataset to a flow based on its internal identifier.

Version: v3

Required Permissions

i **NOTE:** Each request to the Trifacta® platform must include authentication credentials. See *API Authentication*.

Request

Request Type: POST

Endpoint:

```
/v3/importedDatasets/<id>/addToFlow
```

where:

Parameter	Description
<id>	Internal identifier for the imported dataset

Request URI - Example:

```
/v3/importedDatasets/4/addToFlow
```

Request Body:

```
{
  "flow": {
    "id": 4
  }
}
```

Response

Response Status Code - Success: 201 - Created

Response Body:

```

{
  "id": 14,
  "createdBy": 1,
  "updatedBy": 1,
  "scriptId": 7,
  "flowId": 4,
  "wrangled": false,
  "updatedAt": "2017-06-28T19:38:29.275Z",
  "createdAt": "2017-06-28T19:38:29.016Z",
  "flowNodeId": null,
  "deleted_at": null,
  "activesampleId": 15
}

```

Reference

Property	Description
id	Internal identifier for the new wrangled dataset.
createdBy	Internal identifier of the user who created the flow.
updatedBy	Internal identifier of the user who performed the update.
scriptId	Internal identifier for the recipe for the dataset. If <code>null</code> , the dataset has not been wrangled in the Transformer page.
flowId	Internal identifier of the flow that contains this dataset
wrangled	If <code>true</code> , this dataset is a wrangled dataset.
updatedAt	Timestamp for when the dataset was updated.
createdAt	Timestamp for when the dataset was created.
flowNodeId	Internal identifier of the dataset within the flow.
deleted_at	Timestamp for when the dataset was deleted. If <code>null</code> , the dataset has not been deleted.
activesampleId	Internal identifier for the currently active sample for the dataset. If <code>null</code> , there is no currently active sample for the dataset.

For more information on the other properties, see *API ImportedDatasets Get v3*.