

API Releases Create v3

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Create a release for the specified deployment.

Release is created from a local ZIP containing the package of the flow exported from the source system.

NOTE: Releases pertain to Production instances of the Trifacta® platform. For more information, see *Overview of Deployment Management*.

Version: v3

Required Permissions

NOTE: Each request to the Trifacta® platform must include authentication credentials. See *API Authentication*.

Request

Request Type: POST

Endpoint:

```
/v3/deployments/<id>/releases
```

where:

Parameter	Description
<id>	Internal identifier for the deployment

Request URI - Example:

```
/v3/deployments/2/releases
```

Request Body:

The request body must include the following key and value combination submitted as form data:

key	value
data	"@path-to-file"

Example request - curl:

```
curl -X POST \  
  http://example.com:3005/v3/deployments/1/releases \  
  -H 'authorization: Basic c29sc29uQHRyaWZhY3RhLmNvbTphZG1pbG==' \  
  -H 'cache-control: no-cache' \  
  -H 'content-type: multipart/form-data' \  
  -F data=@response.zip
```

Response

Response Status Code - Success: 201 - Created

Response Body Example:

```
{  
  "importRuleChanges": {  
    "object": [],  
    "value": []  
  },  
  "flowName": "POS-r01 Flow"  
}
```

Reference

For more information on import rule changes, see *Define Import Mapping Rules*.