

API Deployments Get v4

This is the latest version of the APIs.

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Get the specified deployment.

NOTE: Deployments pertain to Production instances of the Trifacta® platform. For more information, see *Overview of Deployment Manager*.

Version: v4

Required Permissions

NOTE: Each request to the Trifacta® platform must include authentication credentials. See *API Authentication*.

Request

Request Type: GET

Endpoint:

```
/v4/deployments/<id>
```

where:

Parameter	Description
<id>	Internal identifier for the deployment

Request URI - Example:

```
/v4/deployments/1
```

Query parameter reference:

The following query parameters can be submitted with this endpoint:

Query Parameter	Data Type	Description
embed	string	Comma-separated list of objects to include part of the response.

includeDeleted	string	If set to true, response includes deleted objects.
----------------	--------	--

For more information, see *API Common Query Parameters v4*.

Request Body:

None.

Response

Response Status Code - Success: 200 - OK

Response Body Example:

```
{
  "id": 1,
  "name": "Test Deployment",
  "createdAt": "2019-02-13T20:14:48.537Z",
  "updatedAt": "2019-02-13T20:14:48.537Z",
  "creator": {
    "id": 7
  },
  "updater": {
    "id": 7
  }
}
```

Reference

Property	Description
id	Internal identifier for the deployment
name	Display name for the deployment. This value appears in the user interface.
createdAt	Timestamp for when the deployment was created.
updatedAt	Timestamp for when the deployment was last updated.
creator.id	Internal identifier for the user who created the deployment.
updater.id	Internal identifier for the user who last updated the deployment.