

API Deployments Get ActiveOutputs v4

This is the latest version of the APIs.

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Get active outputs of the specified deployment. When the deployment is run, the listed outputs are generated.

NOTE: Deployments pertain to Production instances of the Trifacta® platform. For more information, see *Overview of Deployment Manager*.

Version: v4

Required Permissions

NOTE: Each request to the Trifacta® platform must include authentication credentials. See *API Authentication*.

Request

Request Type: GET

Endpoint:

```
/v4/deployments/<id>/activeOutputs
```

where:

Parameter	Description
<id>	Internal identifier for the deployment

Request URI - Example:

```
/v4/deployments/1/activeOutputs
```

Request Body:

None.

Response

Response Status Code - Success: 200 - OK

Response Body Example:

```
{
  "data": [
    {
      "outputObjectId": 4,
      "flowNodeId": 22,
      "recipeName": "POS-r01"
    }
  ]
}
```

Reference

Property	Description
outputObjectId	Internal identifier for the active output object You can acquire additional information on this output object. See <i>API OutputObjects Get v4</i> .
flowNodeId	Internal identifier for the recipe to which this output object is attached. <div style="border: 1px solid green; padding: 5px; margin-top: 10px;">Tip: When running a deployment, the flowNodeId value must be passed with the request as the wrangledDataset value. For more information, see <i>API Deployments Run v4</i>.</div>
recipeName	Display name of the recipe.