

API Deployments Run v3



As of Release 6.4, the v3 APIs are End of Life (EOL). Before using this release or a later one, you should migrate to using the latest available API version. For more information, see *API Version Support Matrix*. Latest version of this endpoint: *API Deployments Run v4*.

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Run the job for the active release of the specified deployment.

- At least one manual output must be specified for the main flow within the package. See *Flow View Page*.
- An active release must be specified for the deployment. See *API Releases Patch v3*.

NOTE: Deployments pertain to Production instances of the Trifacta® platform. For more information, see *Overview of Deployment Manager*.

Version: v3

Required Permissions

NOTE: Each request to the Trifacta® platform must include authentication credentials. See *API Authentication*.

Request

Request Type: POST

Endpoint:

```
/v3/deployments/<id>/run
```

where:

Parameter	Description
<id>	Internal identifier for the deployment

Request URI - Example:

```
/v3/deployments/4/run
```

Request Body:

Empty.

Request Body - dataset with parameters:

You can apply parameter overrides when running a deployment. Add the following structure to the request body:

```
{
  "runParameters": {
    "overrides": {
      "data": [
        { "key": "myParamName", "value": "override value"
      }
    ]
  }
}
```

where:

Item	Description
key	Name of parameter to apply to the job run.
value	The string value to assign to the parameter for the job run.

Response

Response Status Code - Success: 201 - Created

Response Body Example:

```
{
  "data": [
    {
      "reason": "JobStarted",
      "sessionId": "dd6a90e0-c353-11e7-ad4e-7f2dd2ae4621",
      "id": 33,
      "jobs": {
        "data": [
          {
            "id": 68
          },
          {
            "id": 69
          },
          {
            "id": 70
          }
        ]
      }
    }
  ]
}
```

Reference

Property	Description
reason	Action undertaken on the endpoint.

sessionId	Internal identifier for the session of the job run
id	JobGroup identifier. For more information, see <i>API JobGroups Get v3</i> .
jobs.data.id	Internal identifier for the individual jobs that compose the job group being executed.