

Configure Automator

Contents:

- *Limitations*
 - *Pre-requisites*
 - *Enable*
 - *Configure*
 - *Database configuration*
-

Using Automator, you can create scheduled executions of your flows in the Trifacta® application. When the schedule is triggered, all datasets that have scheduled output destinations are generated. Results are written to the specified output locations.

Limitations

- You can create one schedule per flow.

Pre-requisites

You must install the two scheduling databases. See *Install Databases for PostgreSQL*.

Enable

By default, the Automator is enabled. Use the following steps to enable or disable.

Steps:

To enable, please specify the following parameters.

You can apply this change through the *Admin Settings Page* (recommended) or

`trifacta-conf.json`

. For more information, see *Platform Configuration Methods*.

```
"feature.scheduling.protobufDefinitionsFolder": "%(topOfTree)s/services/scheduling-service/protobuf/build/install/scheduling-service/api",  
"feature.scheduling.baseUrl": "http://localhost:43143",
```

Parameter	Description
"feature.scheduling.protobufDefinitionsFolder"	Defines the location on the Trifacta node where the protobuf definitions are stored. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">NOTE: Do not modify this value.</div>

"feature.scheduling.baseUrl"	<p>Specify the base URL for the scheduling service. You must specify the full URL:</p> <div style="border: 1px solid #ccc; padding: 5px; margin: 5px 0;"> <pre>http://<base_platform_host>:<scheduling_port></pre> </div> <ul style="list-style-type: none"> • <base_platform_host> is the host of the Trifacta node. Default value is localhost. • <scheduling_port> is the listening port for the scheduling service. Default value is 43143. <div style="border: 1px solid #ccc; padding: 5px; margin: 5px 0; text-align: center;"> <p>NOTE: The value for <scheduling_port> must match the value that you specify for the Scheduling service port. For more information, see <i>System Ports</i>.</p> </div>
------------------------------	---

You apply this change through the *Workspace Settings Page*. For more information, see *Platform Configuration Methods*.

Parameter	Description
Enable Scheduling feature	Set this value to <code>true</code> to enable the Automator.

Configure

Database configuration

You can make changes to the database configuration as needed.

You can apply this change through the *Admin Settings Page* (recommended) or

`trifacta-conf.json`

. For more information, see *Platform Configuration Methods*.

For more information, see *Configure the Databases*.