

KTHLARGESTUNIQUE Function

Extracts the ranked unique value from the values in a column, where $k=1$ returns the maximum value. The value for k must be between 1 and 1000, inclusive. Inputs can be Integer, Decimal, or Datetime.

For purposes of this calculation, two instances of the same value are treated as the same value of k . So, if your dataset contains four rows with column values 10 , 9 , 9 , and 8, then KTHLARGEST returns 9 for $k=2$ and 8 for $k=3$

- For a non-unique version of this function, see *KTHLARGEST Function*.

When used in a pivot transform, the function is computed for each instance of the value specified in the group parameter. See *Pivot Transform*.

Input column can be of Integer, Decimal, or Datetime type. Other values column are ignored. If a row contains a missing or null value, it is not factored into the calculation.

Wrangle vs. SQL: This function is part of Wrangle , a proprietary data transformation language. Wrangle is not SQL. For more information, see *Wrangle Language*.

Basic Usage

```
kthlargestunique(myRating, 3)
```

Output: Returns the third highest unique value from the myRating column.

Syntax and Arguments

```
kthlargestunique(function_col_ref, k_integer) [ group:group_col_ref ] [ limit:limit_count ]
```

Argument	Required?	Data Type	Description
function_col_ref	Y	string	Name of column to which to apply the function
k_integer	Y	integer (positive)	The ranking of the unique value to extract from the source column

For more information on the group and limit parameters, see *Pivot Transform*.

For more information on syntax standards, see *Language Documentation Syntax Notes*.

function_col_ref

Name of the column the values of which you want to calculate the mean. Inputs must be Integer, Decimal, or Datetime values.

NOTE: If the input is in Datetime type, the output is in unixtime format. You can wrap these outputs in the DATEFORMAT function to output the results in the appropriate Datetime format. See *DATEFORMAT Function*.

- Literal values are not supported as inputs.
- Multiple columns and wildcards are not supported.

Usage Notes:

Required?	Data Type	Example Value
Yes	String (column reference)	myValues

k_integer

Integer representing the ranking of the unique value to extract from the source column. Duplicate values are treated as a single value for purposes of this function's calculation.

NOTE: The value for k must be an integer between 1 and 1,000 inclusive.

- k=1 represents the maximum value in the column.
- If k is greater than or equal to the number of values in the column, the minimum value is returned.
- Missing and null values are not factored into the ranking of k.

Usage Notes:

Required?	Data Type	Example Value
Yes	Integer (positive)	4

Examples

Tip: For additional examples, see *Common Tasks*.

This example explores how you can use aggregation functions to calculate rank of values in a column using the KTHLARGEST and KTHLARGESTUNIQUE functions.

- See *KTHLARGEST Function*.
- See *KTHLARGESTUNIQUE Function*.

Source:

You have a set of student test scores:

Student	Score
Anna	84
Ben	71
Caleb	76
Danielle	87
Evan	85
Faith	92
Gabe	87
Hannah	99

Ian	73
Jane	68

Transformation:

You can use the following transformations to extract the 1st through 4th-ranked scores on the test:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	KTHLARGEST(Score, 1)
Parameter: New column name	'1st'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	KTHLARGEST(Score, 2)
Parameter: New column name	'2nd'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	KTHLARGEST(Score, 3)
Parameter: New column name	'3rd'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	KTHLARGEST(Score, 4)
Parameter: New column name	'4th'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	KTHLARGESTUNIQUE(Score, 3)
Parameter: New column name	'3rdUnique'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	KTHLARGESTUNIQUE(Score, 4)

Parameter: New column name	'4thUnique'
----------------------------	-------------

Results:

When you reorganize the columns, the dataset might look like the following:

Student	Score	1st	2nd	3rd	4th	3rdUnique	4thUnique
Anna	84	99	92	87	87	87	85
Ben	71	99	92	87	87	87	85
Caleb	76	99	92	87	87	87	85
Danielle	87	99	92	87	87	87	85
Evan	85	99	92	87	87	87	85
Faith	92	99	92	87	87	87	85
Gabe	87	99	92	87	87	87	85
Hannah	99	99	92	87	87	87	85
Ian	73	99	92	87	87	87	85
Jane	68	99	92	87	87	87	85

Notes:

- The value 87 is both the third and fourth scores.
 - For the KTHLARGEST function, it is the output for the third and fourth ranking.
 - For the KTHLARGESTUNIQUE function, it is the output for the third ranking only.