

# Configure AWS Per-User Authentication

**Contents:**

- *Enable*
- *Configure Per-User Authentication using IAM Role*
- *User Access*

---

For Trifacta Wrangler Enterprise, you can configure AWS authentication on a per-user basis, using temporary credentials for superior security.

## Enable

The following parameters must be set:

Property	Description
<pre>"aws.readFromConfigurationService": false,</pre>	Set this value to <code>false</code> for Trifacta Wrangler Enterprise, which prevents the product from retrieving AWS-related configuration information from the incorrect source.
<pre>"aws.mode": "user",</pre>	Each user can specify credentials.

To authenticate to AWS services from the Trifacta platform using an IAM role:

Property	Description
----------	-------------

<pre>"aws.ec2InstanceRoleForAssumeRole": true,</pre>	<ul style="list-style-type: none"> <li>If <code>true</code>, then all users use the EC2 instance role for authenticating to the AWS STS service for their temporary credentials.</li> </ul> <div data-bbox="464 264 1455 344" style="border: 1px solid #ccc; padding: 5px; margin: 10px 0;"> <p><b>NOTE:</b> You must ensure that the role provides adequate access to STS. Details are below.</p> </div> <div data-bbox="464 369 1455 449" style="border: 1px solid #ccc; padding: 5px; margin: 10px 0; background-color: #e6f2e6;"> <p><b>Tip:</b> This method is recommended.</p> </div> <ul style="list-style-type: none"> <li>If <code>false</code>, then a system-wide set of AWS key/secret credentials must be inserted into platform configuration in the Admin Settings page as the master set of credentials to access STS for temporary credentials:</li> </ul> <p>Properties to set:</p> <div data-bbox="464 621 1455 716" style="border: 1px solid #ccc; padding: 5px; margin: 10px 0;"> <pre>"aws.s3.key" "aws.s3.secret"</pre> </div> <div data-bbox="464 741 1455 829" style="border: 1px solid #ccc; padding: 5px; margin: 10px 0;"> <p><b>NOTE:</b> After specifying the above key/secret combination, you can skip to the User Access section below.</p> </div>
--	---

### Configure Per-User Authentication using IAM Role

Please complete the following general steps.

**Steps:**

1. Instance role: Create an IAM role and link it to the EC2 instance where the Trifacta node is hosted. Include the following IAM policy:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "VisualEditor0",
      "Effect": "Allow",
      "Action": "sts:AssumeRole",
      "Resource": "arn:aws:iam::*:role/*"
    }
  ]
}
```

2. User role: Create another IAM role and provides required access to the S3 buckets. Example:

```

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "MyBucketAndObjectPermissions",
      "Action": [
        "s3:GetBucketLocation",
        "s3:ListBucket",
        "s3:DeleteObject",
        "s3:GetObject",
        "s3:PutObject"
      ],
      "Effect": "Allow",
      "Resource": [
        "arn:aws:s3:::<my_s3_bucket>",
        "arn:aws:s3:::<my_s3_bucket>/*"
      ]
    },
    {
      "Sid": "TrifactaPublicDatasets",
      "Effect": "Allow",
      "Action": [
        "s3:GetObject",
        "s3:ListBucket"
      ],
      "Resource": [
        "arn:aws:s3:::trifacta-public-datasets/*",
        "arn:aws:s3:::trifacta-public-datasets"
      ]
    }
  ]
}

```

where:

<my\_s3\_bucket> is the name of your bucket.

3. Under the user role definition, edit the Trust relationship. Add the instance role to Principal:

```

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": {
        "AWS": [
          "arn:aws:iam::          awsAccountId:role/instanceRole"
        ]
      },
      "Action": "sts:AssumeRole"
    }
  ]
}

```

- a. For more information, see *Insert Trust Relationship in AWS IAM Role*.
- b. For more granular control over the Trust relationship, see [https://docs.aws.amazon.com/IAM/latest/UserGuide/reference\\_policies\\_elements\\_principal.html](https://docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_elements_principal.html).
4. AWS Glue: If you are integrating with AWS Glue, additional permissions must be set. For more information, see *Enable AWS Glue Access*.
5. Log in the Trifacta platform as a Trifacta admin.
6. Click the link to specify storage settings. Populate the values for:
  - a. IAM role
  - b. Role ARN
  - c. S3 Bucket Name

7. Save your changes.

## User Access

After per-user authentication has been enabled, each user must provide or be provided the credentials and S3 bucket to use. Users can insert a default S3 bucket and credentials to use in their profiles. See *Configure Your Access to S3*.