

API Deployments Get v3

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Get the specified deployment.

i **NOTE:** Deployments pertain to Production instances of the Trifacta® platform. For more information, see *Overview of Deployment Management*.

Version: v3

Required Permissions

i **NOTE:** Each request to the Trifacta® platform must include authentication credentials. See *API Authentication*.

Request

Request Type: GET

Endpoint:

```
/v3/deployments/<id>
```

where:

Parameter	Description
<id>	Internal identifier for the deployment

Request URI - Example:

```
/v3/deployments/3
```

Request Body:

Empty.

Response

Response Status Code - Success: 200 - OK

Response Body Example:

```
{
  "id": 3,
  "name": "Payments Deployment",
  "createdAt": "2017-09-27T07:00:00.000Z",
  "updatedAt": "2017-09-30T00:17:00.079Z",
  "createdBy": 1,
  "updatedBy": 2
}
```

Reference

Property	Description
id	Internal identifier for the deployment
name	Display name for the deployment. This value appears in the user interface.
createdAt	Timestamp for when the deployment was created.
updatedAt	Timestamp for when the deployment was last updated.
createdBy	Internal identifier for the user who created the deployment.
updatedBy	Internal identifier for the user who last updated the deployment.