

API WrangledDatasets Get v4

This is the latest version of the APIs.

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Get the specified wrangled dataset.

Tip: In the Trifacta application UI, the `WrangledDataset` object is called a `recipe`.

Version: v4

Required Permissions

NOTE: Each request to the Trifacta® platform must include authentication credentials. See *API Authentication*.

Request

Request Type: GET

Endpoint:

```
/v4/wrangledDatasets/<id>
```

Endpoint with embedded reference:

Use the following endpoint to embed information about the flow that contains the dataset in the response body.

```
/v4/wrangledDatasets/<id>?embed=flow
```

where:

Parameter	Description
<id>	Internal identifier for the wrangled dataset

Request URI - Example:

```
/v4/wrangledDatasets/6/
```

Query parameter reference:

The following query parameters can be submitted with this endpoint:

Query Parameter	Data Type	Description
embed	string	Comma-separated list of objects to include part of the response.
includeDeleted	string	If set to true, response includes deleted objects.

For more information, see *API Common Query Parameters v4*.

Request Body:

Empty.

Response

Response Status Code - Success: 200 - OK

Response Body Example:

```
{
  "id": 6,
  "wrangled": true,
  "createdAt": "2018-02-06T19:43:02.791Z",
  "updatedAt": "2018-02-06T19:43:02.838Z",
  "recipe": {
    "id": 6
  },
  "name": "POS-r01",
  "description": null,
  "referenceInfo": null,
  "activeSample": {
    "id": 6
  },
  "creator": {
    "id": 1
  },
  "updater": {
    "id": 1
  },
  "flow": {
    "id": 1
  }
}
```

Response Body Example with embedded reference:

```

{
  "id": 6,
  "wrangled": true,
  "createdAt": "2018-02-06T19:43:02.791Z",
  "updatedAt": "2018-02-06T19:43:02.838Z",
  "flow": {
    "id": 1,
    "name": "2013 POS",
    "description": null,
    "createdAt": "2018-02-06T19:42:55.091Z",
    "updatedAt": "2018-02-06T19:42:55.091Z",
    "creator": {
      "id": 1
    },
    "updater": {
      "id": 1
    }
  },
  "recipe": {
    "id": 6
  },
  "name": "POS-r01",
  "description": null,
  "referenceInfo": null,
  "activeSample": {
    "id": 6
  },
  "creator": {
    "id": 1
  },
  "updater": {
    "id": 1
  }
}

```

Reference

Wrangled Dataset:

These properties apply to the source of the wrangled dataset.

Property	Description
id	Internal identifier of the wrangled dataset
wrangled	If <code>true</code> , this dataset is a wrangled dataset
createdAt	Timestamp for when the dataset was imported
updatedAt	Timestamp for when the dataset was last updated
script	Internal identifier of the recipe associated with this dataset
name	Internal name of the wrangled dataset
description	User-friendly description for the wrangled dataset
activeSample	Internal identifier of the currently active sample for this dataset
creator	Internal identifier of the user who created the wrangled dataset
updater	Internal identifier of the user who last updated the wrangled dataset
flow	Internal identifier of the flow that contains this dataset

Embedded Flow:

For more information on the embedded flow properties, see *API Flows Get v4*.