

Configure Scheduling

Contents:

- *Limitations*
- *Pre-requisites*
- *Enable*
- *Configure*
 - *Database configuration*

You can create scheduled executions of your flows. When the schedule is triggered, all datasets that have scheduled output destinations are generated. Results are written to the specified output locations.

Limitations

- You can create one schedule per flow.

Pre-requisites

You must install the two scheduling databases. See *Install the Databases*.

Enable

By default, scheduling is enabled. Use the following steps to enable or disable.

Steps:


To enable, please specify the following parameters.


You can apply this change through the *Admin Settings Page* (recommended) or

`trifacta-conf.json`

. For more information, see *Platform Configuration Methods*.

```
"feature.scheduling.enabled": true,  
"feature.scheduling.protobufDefinitionsFolder": "%(topOfTree)s/services/scheduling-service/protobuf/build  
/install/scheduling-service/api",  
"feature.scheduling.baseUrl": "http://localhost:43143",
```

Parameter	Description
"feature.scheduling.enabled"	Set this value to <code>true</code> to enable scheduling.
"feature.scheduling.protobufDefinitionsFolder"	Defines the location on the Trifacta node where the protobuf definitions are stored. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> NOTE: Do not modify this value.</div>

"feature.scheduling. baseUrl"	<p>Specify the base URL for the scheduling service. You must specify the full URL:</p> <pre>http://<base_platform_host>:<scheduling_port></pre> <ul style="list-style-type: none">• <base_platform_host> is the host of the Trifacta node. Default value is localhost .• <scheduling_port> is the listening port for the scheduling service. Default value is 43143. <div style="border: 1px solid #ccc; padding: 5px;"><p> NOTE: The value for <scheduling_port> must match the value that you specify for the Scheduling service port. For more information, see <i>System Ports</i>.</p></div>
----------------------------------	--

Configure

Database configuration

You can make changes to the database configuration as needed.

You can apply this change through the *Admin Settings Page* (recommended) or

`trifacta-conf.json`

. For more information, see *Platform Configuration Methods*.

For more information, see *Configure the Databases*.