

EXAMPLE - Case Functions

Source:

In the following example, you can see a number of input values in the leftmost column. The output columns are blank.

| input | uppercase | lowercase | propercase |
|--|-----------|-----------|------------|
| AbCdEfGh IjKlMnO | | | |
| go West, young man! | | | |
| Oh, *(\$%(&! That HURT! | | | |
| A11 w0rk and n0 0play makes Jack a dull boy. | | | |

Transformation:

To generate uppercase, lowercase, and propercase values in the output columns, use the following transforms:

| | |
|----------------------------|--------------------------|
| Transformation Name | Edit column with formula |
| Parameter: Columns | uppercase |
| Parameter: Formula | UPPER(input) |

| | |
|----------------------------|--------------------------|
| Transformation Name | Edit column with formula |
| Parameter: Columns | lowercase |
| Parameter: Formula | LOWER(input) |

| | |
|----------------------------|--------------------------|
| Transformation Name | Edit column with formula |
| Parameter: Columns | propercase |
| Parameter: Formula | PROPER(input) |

Results:

| input | uppercase | lowercase | propercase |
|--|--|--|--|
| AbCdEfGh IjKlMnO | ABCDEFGH IJKLMNO | abcdefgh ijklmno | Abcdefgh Ijklmno |
| go West, young man! | GO WEST, YOUNG MAN! | go west, young man! | Go West, Young Man! |
| Oh, *(\$%(&! That HURT! | OH, *(\$%(&! THAT HURT! | oh, *(\$%(&! that hurt! | Oh, *(\$%(&! That Hurt! |
| A11 w0rk and n0 0play makes Jack a dull boy. | A11 W0RK AND N0 0PLAY MAKES JACK A DULL BOY. | a11 w0rk and n0 0play makes jack a dull boy. | A11 W0rk And N0 0play Makes Jack A Dull Boy. |