

IFMISMATCHED Function

Contents:

- *Basic Usage*
- *Syntax and Arguments*
 - *source_value*
 - *datatype_literal*
 - *output_value*
- *Examples*
 - *Example - IF* functions for data type validation*

The IFMISMATCHED function writes out a specified value if the input expression does not match the specified data type or typing array. Otherwise, it writes the source value. Input can be a literal, a column reference, or a function.

The ISMISMATCHED function simply tests if a value is mismatched. See *ISMISMATCHED Function*.

Wrangle vs. SQL: This function is part of Wrangle, a proprietary data transformation language. Wrangle is not SQL. For more information, see *Wrangle Language*.

Basic Usage

Basic data type:

```
ifmismatched(my_ssn, 'SSN', 'XXX-XX-XXXX')
```

Output: Returns the value XXX-XX-XXXX if the value in my_ssn does not match the SSN data type.

Data type with formatting options:

For data types with formatting options, such as Datetime, you can specify the format using an array, as in the following:

```
ifmismatched(month_Date, ['Datetime', 'mm-dd-yy', 'mm*dd*yy'], null())
```

Output: Returns null if values in month_Date are mismatched against Datetime values in the mm-dd-yy or mm*dd*yy formats.

Syntax and Arguments

```
ifmismatched(column_string, data_type_literal, computed_value)
```

Argument	Required?	Data Type	Description
source_value	Y	string	Name of column, string literal or function to be tested
datatype_literal	Y	string	String literal or array that identifies the data type against which to validate the source values
output_value	y	string	String literal value to write

For more information on syntax standards, see *Language Documentation Syntax Notes*.

source_value

Name of the column, string literal, or function to be tested for data type matches.

- Missing literals or column values generate missing string results.
- Multiple columns and wildcards are not supported.

Usage Notes:

Required?	Data Type	Example Value
Yes	String literal, column reference, or function	myColumn

datatype_literal

Literal value or string array that identifies data type to which to validate the source column or string.

- Column references are not supported.

Usage Notes:

Required?	Data Type	Example Value
Yes	String literal	'Integer'

Valid data type strings:

When referencing a data type within a transform, you can use the following strings to identify each type:

NOTE: In Wrangle transforms, these values are case-sensitive.

NOTE: When specifying a data type by name, you must use the String value listed below. The Data Type value is the display name for the type.

Data Type	String
String	'String'
Integer	'Integer'
Decimal	'Float'
Boolean	'Bool'
Social Security Number	'SSN'
Phone Number	'Phone'
Email Address	'Emailaddress'
Credit Card	'Creditcard'
Gender	'Gender'

Object	'Map'
Array	'Array'
IP Address	'Ipaddress'
URL	'Url'
HTTP Code	'Httpcodes'
Zip Code	'Zipcode'
State	'State'
Date / Time	'Datetime'

output_value

The output value to write if the tested value is mismatched for the specified data type.

Usage Notes:

Required?	Data Type	Example Value
Yes	String or numeric literal	'Data type mismatch'

Examples

Tip: For additional examples, see *Common Tasks*.

Example - IF* functions for data type validation

This example illustrates how to use the IF* functions for data type validation.

Functions:

Item	Description
IFNULL Function	The IFNULL function writes out a specified value if the source value is a null. Otherwise, it writes the source value. Input can be a literal, a column reference, or a function.
IFMISSING Function	The IFMISSING function writes out a specified value if the source value is a null or missing value. Otherwise, it writes the source value. Input can be a literal, a column reference, or a function.
IFMISMATCHED Function	The IFMISMATCHED function writes out a specified value if the input expression does not match the specified data type or typing array. Otherwise, it writes the source value. Input can be a literal, a column reference, or a function.
IFVALID Function	The IFVALID function writes out a specified value if the input expression matches the specified data type. Otherwise, it writes the source value. Input can be a literal, a column reference, or a function.
MERGE Function	Merges two or more columns of String type to generate output of String type. Optionally, you can insert a delimiter between the merged values.

Source:

The following simple table lists zip codes by customer identifier:

custId	custZip
--------	---------

C001	98123
C002	94105
C003	12415
C004	12451-2234
C005	12441-298
C006	
C007	
C008	1242
C009	1104

Transformation:

When the above is imported into the Transformer page, you notice the following:

- The `custZip` column is typed as Integer.
- There are two missing and two mismatched values in the `custZip` column.

First, you test for valid values in the `custZip` column. Using the `IFVALID` function, you can validate against any data type:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	<code>IFVALID(custZip, 'Zipcode', 'ok')</code>
Parameter: New column name	'status'

Fix four-digit zips: In the `status` column are instances of `ok` for the top four rows. You notice that the bottom two rows contain four-digit codes.

Since the `custZip` values were originally imported as Integer, any leading 0 values are deleted. In this case, you can add back the leading zero. Before the previous step, change the data type of `zip` to String and insert the following:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	<code>IF(LEN(custZip)==4, '0', '')</code>
Parameter: New column name	'FourDigitZip'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	<code>MERGE([FourDigitZip, custZip])</code>
Parameter: New column name	'custZip2'

Transformation Name	Edit column with formula
Parameter: Columns	zip
Parameter: Formula	custZip2

Transformation Name	Delete columns
Parameter: Columns	FourDigitZip,custZip2
Parameter: Action	Delete selected columns

Now, when you click the last recipe step, you should see that two more rows in `status` are listed as `Ok`.

For the zip code with the three-digit extension, you can simply remove that extension to make it valid. Click the step above the last one. In the data grid, highlight the value. Click the Replace suggestion card. Select the option that uses the following for the matching pattern:

```
'-{\digit}{3}{end}'
```

The above means that all three-digit extensions are deleted from the zip. You can do the same for any two- and one-digit extensions, although there are none in this sample.

Missing and null values: Now, you need to address how to handle missing and null values. The `IFMISSING` tests for both missing and null values, while the `IFNULL` tests just for null values. In this example, you want to delete null values, which could mean that the data for that row is malformed and to write a status of `missing` for missing values.

Click above the last line in the recipe to insert the following:

Transformation Name	Edit column with formula
Parameter: Columns	custZip
Parameter: Formula	IFNULL(custZip, 'xxxxx')

Transformation Name	Edit column with formula
Parameter: Columns	custZip
Parameter: Formula	IFMISSING(custZip, '00000')

Now, when you click the last line of the recipe, only the null value is listed as having a status other than `ok`. You can use the following to remove this row and all like it:

Transformation Name	Filter rows
Parameter: Condition	Custom formula
Parameter: Type of formula	Custom single
Parameter: Condition	(status == 'xxxxx')
Parameter: Action	Delete matching rows

Results:

custId	custZip	status
C001	98123	ok
C002	94105	ok
C003	12415	ok
C004	12451-2234	ok
C005	12441-298	ok
C006	00000	ok
C008	1242	ok
C009	1104	ok

As an exercise, you might repeat the above steps starting with the IFMISMATCHED function determining the value in the status column:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	IFMISMATCHED(custZip, 'Zipcode', 'mismatched')
Parameter: New column name	'status'