

AVERAGEIF Function

Contents:

- *Basic Usage*
- *Syntax and Arguments*
 - *col_ref*
 - *test_expression*
- *Examples*
 - *Example - Conditional Calculation Functions*

Generates the average value of rows in each group that meet a specific condition. Generated value is of Decimal type.

NOTE: When added to a transformation, this function is applied to the current sample. If you change your sample or run the job, the computed values for this function are updated. Transformations that change the number of rows in subsequent recipe steps do not affect the values computed for this step.

To perform a simple averaging of rows without conditionals, use the `AVERAGE` function. See *AVERAGE Function*.

Basic Usage

```
averageif(fineValue, finesCount >= 3)
```

Output: Generates a two-column table containing the unique values for `postal_code` and the average of the `fineValue` column for that `postal_code` value when the `finesCount` is greater than or equal to 3. The `limit` parameter defines the maximum number of output columns.

Syntax and Arguments

```
averageif(col_ref, test_expression) [group:group_col_ref] [limit:limit_count]
```

Argument	Required?	Data Type	Description
<code>col_ref</code>	Y	string	Reference to the column you wish to evaluate.
<code>test_expression</code>	Y	string	Expression that is evaluated. Must resolve to <code>true</code> or <code>false</code>

For more information on syntax standards, see *Language Documentation Syntax Notes*.

For more information on the `group` and `limit` parameter, see *Pivot Transform*.

col_ref

Name of the column whose values you wish to use in the calculation. Column must be a numeric (Integer or Decimal) type.

Usage Notes:

Required?	Data Type	Example Value
-----------	-----------	---------------

Yes	String that corresponds to the name of the column	myValues
-----	---	----------

test_expression

This parameter contains the expression to evaluate. This expression must resolve to a Boolean (`true` or `false`) value.

Usage Notes:

Required?	Data Type	Example Value
Yes	String expression that evaluates to <code>true</code> or <code>false</code>	<code>(LastName == 'Mouse' && FirstName == 'Mickey')</code>

Examples

Tip: For additional examples, see *Common Tasks*.

Example - Conditional Calculation Functions

This example illustrates how you can use the following conditional calculation functions to analyze weather data:

- **AVERAGEIF** - Average of a set of values by group that meet a specified condition. See *AVERAGEIF Function*.
- **MINIF** - Minimum of a set of values by group that meet a specified condition. See *MINIF Function*.
- **MAXIF** - Maximum of a set of values by group that meet a specified condition. See *MAXIF Function*.
- **VARIF** - Variance of a set of values by group that meet a specified condition. See *VARIF Function*.
- **STDEVIF** - Standard deviation of a set of values by group that meet a specified condition. See *STDEVIF Function*.

Source:

Here is some example weather data:

date	city	rain	temp	wind
1/23/17	Valleyville	0.00	12.8	6.7
1/23/17	Center Town	0.31	9.4	5.3
1/23/17	Magic Mountain	0.00	0.0	7.3
1/24/17	Valleyville	0.25	17.2	3.3
1/24/17	Center Town	0.54	1.1	7.6
1/24/17	Magic Mountain	0.32	5.0	8.8
1/25/17	Valleyville	0.02	3.3	6.8
1/25/17	Center Town	0.83	3.3	5.1
1/25/17	Magic Mountain	0.59	-1.7	6.4
1/26/17	Valleyville	1.08	15.0	4.2
1/26/17	Center Town	0.96	6.1	7.6
1/26/17	Magic Mountain	0.77	-3.9	3.0

1/27/17	Valleyville	1.00	7.2	2.8
1/27/17	Center Town	1.32	20.0	0.2
1/27/17	Magic Mountain	0.77	5.6	5.2
1/28/17	Valleyville	0.12	-6.1	5.1
1/28/17	Center Town	0.14	5.0	4.9
1/28/17	Magic Mountain	1.50	1.1	0.4
1/29/17	Valleyville	0.36	13.3	7.3
1/29/17	Center Town	0.75	6.1	9.0
1/29/17	Magic Mountain	0.60	3.3	6.0

Transformation:

The following computes average temperature for rainy days by city:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	AVERAGEIF(temp, rain > 0)
Parameter: Group rows by	city
Parameter: New column name	'avgTempWRain'

The following computes maximum wind for sub-zero days by city:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	MAXIF(wind,temp < 0)
Parameter: Group rows by	city
Parameter: New column name	'maxWindSubZero'

This step calculates the minimum temp when the wind is less than 5 mph by city:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	MINIF(temp,wind<5)
Parameter: Group rows by	city
Parameter: New column name	'minTempWind5'

This step computes the variance in temperature for rainy days by city:

Transformation Name	New formula
----------------------------	-------------

Parameter: Formula type	Single row formula
Parameter: Formula	VARIF(temp,rain >0)
Parameter: Group rows by	city
Parameter: New column name	'varTempWRain'

The following computes the standard deviation in rainfall for Center Town:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	STDEVIF(rain,city=='Center Town')
Parameter: Group rows by	city
Parameter: New column name	'stDevRainCT'

You can use the following transforms to format the generated output. Note the \$col placeholder value for the multi-column transforms:

Transformation Name	Edit column with formula
Parameter: Columns	stDevRainCenterTown,maxWindSubZero
Parameter: Formula	numformat(\$col,'##.##')

Since the following rely on data that has only one significant digit, you should format them differently:

Transformation Name	Edit column with formula
Parameter: Columns	varTempWRain,avgTempWRain,minTempWind5
Parameter: Formula	numformat(\$col,'##.#')

Results:

date	city	rain	temp	wind	avgTempWRain	maxWindSubZero	minTempWind5	varTempWRain	stDevRain
1/23 /17	Valley ville	0.00	12.8	6.7	8.3	5.1	7.2	63.8	0.37
1/23 /17	Center Town	0.31	9.4	5.3	7.3		5	32.6	0.37
1/23 /17	Magic Mountain	0.00	0.0	7.3	1.6	6.43	-3.9	12	0.37
1/24 /17	Valley ville	0.25	17.2	3.3	8.3	5.1	7.2	63.8	0.37
1/24 /17	Center Town	0.54	1.1	7.6	7.3		5	32.6	0.37
1/24 /17	Magic Mountain	0.32	5.0	8.8	1.6	6.43	-3.9	12	0.37

1/25 /17	Valley ville	0.02	3.3	6.8	8.3	5.1	7.2	63.8	0.37
1/25 /17	Cente r Town	0.83	3.3	5.1	7.3		5	32.6	0.37
1/25 /17	Magic Mount ain	0.59	-1.7	6.4	1.6	6.43	-3.9	12	0.37
1/26 /17	Valley ville	1.08	15.0	4.2	8.3	5.1	7.2	63.8	0.37
1/26 /17	Cente r Town	0.96	6.1	7.6	7.3		5	32.6	0.37
1/26 /17	Magic Mount ain	0.77	-3.9	3.0	1.6	6.43	-3.9	12	0.37
1/27 /17	Valley ville	1.00	7.2	2.8	8.3	5.1	7.2	63.8	0.37
1/27 /17	Cente r Town	1.32	20.0	0.2	7.3		5	32.6	0.37
1/27 /17	Magic Mount ain	0.77	5.6	5.2	1.6	6.43	-3.9	12	0.37
1/28 /17	Valley ville	0.12	-6.1	5.1	8.3	5.1	7.2	63.8	0.37
1/28 /17	Cente r Town	0.14	5.0	4.9	7.3		5	32.6	0.37
1/28 /17	Magic Mount ain	1.50	1.1	0.4	1.6	6.43	-3.9	12	0.37
1/29 /17	Valley ville	0.36	13.3	7.3	8.3	5.1	7.2	63.8	0.37
1/29 /17	Cente r Town	0.75	6.1	9.0	7.3		5	32.6	0.37
1/29 /17	Magic Mount ain	0.60	3.3	6.0	1.6	6.43	-3.9	12	0.37