

COUNTA Function

Generates the count of non-null rows in a specified column, optionally counted by group. Generated value is of Integer type.

NOTE: Empty string values are counted. Null values are not counted.

NOTE: When added to a transformation, this function calculates the number of values in the specified column, as displayed in the current sample. Counts are not applied to the entire dataset until you run the job. If you change your sample or run the job, the computed values for this function are updated. Transformations that change the number of rows in subsequent recipe steps do not affect the value for the already computed instance of COUNTA.

For a version of this function computed over a rolling window of rows, see *ROLLINGCOUNTA Function*.

Wrangle vs. SQL: This function is part of Wrangle , a proprietary data transformation language. Wrangle is not SQL. For more information, see *Wrangle Language*.

Basic Usage

```
counta(name)
```

Output: Returns the count of non-empty values in the `name` column.

Syntax and Arguments

```
counta(function_col_ref) [group:group_col_ref] [limit:limit_count]
```

Argument	Required?	Data Type	Description
function_col_ref	Y	string	Name of column to which to apply the function

For more information on the `group` parameter, see *Pivot Transform*.

function_col_ref

Name of the column from which to count values based on the grouping.

- Literal values are not supported as inputs.
- Multiple columns and wildcards are not supported.

Usage Notes:

Required?	Data Type	Example Value
Yes	String (column reference)	myValues

Examples

Tip: For additional examples, see *Common Tasks*.

Example - Simple row count

This example demonstrates how to count the number of values and non-null values within a group.

Functions:

Item	Description
COUNTA Function	Generates the count of non-null rows in a specified column, optionally counted by group. Generated value is of Integer type.
COUNTDISTINCT Function	Generates the count of distinct values in a specified column, optionally counted by group. Generated value is of Integer type.

Source:

In the following example, the seventh row is an empty string, and the eighth row is a null value.

rowId	Val
r001	val1
r002	val1
r003	val1
r004	val2
r005	val2
r006	val3
r007	(empty)
r008	(null)

Transformation:

Apply a COUNTA function on the source column:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	COUNTA(Val)
Parameter: New column name	'fctnCounta'

Apply a COUNTDISTINCT function on the source:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	COUNTDISTINCT(Val)

Parameter: New column name	'fctnCountdistinct'
-----------------------------------	---------------------

Results:

Below, both functions count the number of values in the column, with COUNTDISTINCT counting distinct values only. The empty value for r007 is counted by both functions.

rowId	Val	fctnCountdistinct	fctnCounta
r001	val1	4	7
r002	val1	4	7
r003	val1	4	7
r004	val2	4	7
r005	val2	4	7
r006	val3	4	7
r007	(empty)	4	7
r008	(null)	4	7