

EXAMPLE - Type Functions

This example illustrates how various type checking functions can be applied to your data.

- `ISVALID` - Returns `true` if the input matches the specified data type. See *VALID Function*.
- `ISMISMATCHED` - Returns `true` if the input does not match the specified data type. See *ISMISMATCHED Function*.
- `ISMISSING` - Returns `true` if the input value is missing. See *ISMISSING Function*.
- `ISNULL` - Returns `true` if the input value is null. See *ISNULL Function*.
- `NULL` - Generates a null value. See *NULL Function*.

Source:

Some source values that should match the State and Integer data types:

State	Qty
CA	10
OR	-10
WA	2.5
ZZ	15
ID	
	4

Transformation:

Invalid State values: You can test for invalid values for State using the following:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	<code>ISMISMATCHED (State, 'State')</code>

The above transform flags rows 4 and 6 as mismatched.

NOTE: A missing value is not valid for a type, including String type.

Invalid Integer values: You can test for valid matches for Qty using the following:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	<code>(ISVALID (Qty, 'Integer') && (Qty > 0))</code>
Parameter: New column name	<code>'valid_Qty'</code>

The above transform flags as valid all rows where the `Qty` column is a valid integer that is greater than zero.

Missing values: The following transform tests for the presence of missing values in either column:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	(ISMISSING(State) ISMISSING(Qty))
Parameter: New column name	'missing_State_Qty'

After re-organizing the columns using the `move` transform, the dataset should now look like the following:

State	Qty	mismatched_State	valid_Qty	missing_State_Qty
CA	10	false	true	false
OR	-10	false	false	false
WA	2.5	false	false	false
ZZ	15	true	true	false
ID		false	false	true
	4	false	true	true

Since the data does not contain null values, the following transform generates null values based on the preceding criteria:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	((mismatched_State == 'true') (valid_Qty == 'false') (missing_State_Qty == 'true')) ? NULL() : 'ok'
Parameter: New column name	'status'

You can then use the `ISNULL` check to remove the rows that fail the above test:

Transformation Name	Filter rows
Parameter: Condition	Custom formula
Parameter: Type of formula	Custom single
Parameter: Condition	ISNULL('status')
Parameter: Action	Delete matching rows

Results:

Based on the above tests, the output dataset contains one row:

State	Qty	mismatched_State	valid_Qty	missing_State_Qty	status
CA	10	false	true	false	ok