

API Releases Get v3

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Get the specified release.

i **NOTE:** Releases pertain to Production instances of the Trifacta® platform. For more information, see *Overview of Deployment Management*.

Version: v3

Required Permissions

i **NOTE:** Each request to the Trifacta® platform must include authentication credentials. See <https://api.trifacta.com/ee/5.1/index.html#section/Authentication>.

Request

Request Type: GET

Endpoint:

```
/v3/releases/<id>
```

where:

Parameter	Description
<id>	Internal identifier for the release

Request URI - Example:

```
/v3/releases/2
```

Request Body:

Empty.

Response

Response Status Code - Success: 200 - OK

Response Body Example:

```
{
  "id": 2,
  "notes": "My second release",
  "packageUuid": "b6b76bc0-alc6-11e7-8c9d-f53cb0bb7b0a",
  "active": null,
  "createdAt": "2017-08-01T07:00:00.000Z",
  "updatedAt": "2017-10-05T12:26:36.326Z",
  "deploymentId": 1,
  "createdBy": 1,
  "updatedBy": 2
}
```

Reference

Property	Description
id	Internal identifier for the release
notes	Display value for notes that you can add to describe the release
packageUuid	Internal identifier for the package
active	If <code>true</code> , the release is the active one for the deployment. If set to <code>null</code> , the release is not active.
createdAt	Timestamp for when the release was created.
updatedAt	Timestamp for when the release was last updated.
createdBy	Internal identifier for the user who created the release.
updatedBy	Internal identifier for the user who last updated the release.