

# API People Get v4

✔ This is the latest version of the APIs.

## Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Retrieve the platform account information for a user specified by userId.

**Version:** v4

## Required Permissions

The authenticated user must be an admin.

**NOTE:** Each request to the Designer Cloud powered by Trifacta® platform must include authentication credentials. See <https://api.trifacta.com/ee/6.0/index.html#section/Authentication>.

## Request

**Request Type:** GET

## Endpoint:

```
/v4/people/<id>
```

where:

Parameter	Description
<id>	Internal identifier of the user to retrieve.

## Request URI - Example:

```
/v4/people/4
```

## Request Body:

Empty.

## Response

**Response Status Code - Success:** 200 - OK

## Response Body Example:

```

{
  "id": 2,
  "email": "joe@example.com",
  "name": "Joe Guy",
  "ssoPrincipal": null,
  "hadoopPrincipal": null,
  "isAdmin": false,
  "isDisabled": false,
  "forcePasswordChange": false,
  "state": "active",
  "lastStateChange": null,
  "createdAt": "2019-02-12T09:04:52.073Z",
  "updatedAt": "2019-02-12T09:04:52.073Z",
  "outputHomeDir": "/trifacta/queryResults/joe@example.com",
  "fileUploadPath": "/trifacta/uploads",
  "lastLoginTime": "2019-05-19T10:53:11.014Z",
  "awsConfig": null
}

```

## Reference

Property	Description
id	Internal user identifier
email	Email address (and loginId) for the user
name	Display name for the user
ssoPrincipal	(If SSO is enabled) Principal value of the user for single-sign on
hadoopPrincipal	(If secure impersonation is enabled) Hadoop principal value for the user, which determines permissions on the cluster
isAdmin	If <code>true</code> , the user account is an administrator account.
isDisabled	If <code>true</code> , the account is disabled.
forcePasswordChange	(if enabled) When set to <code>true</code> , the user must change the account password on next login.
state	Current state of the user account: <ul style="list-style-type: none"> <li><code>active</code> - user is active and usable in the workspace</li> <li><code>hidden</code> - user account has been hidden from use.</li> </ul>
lastStateChange	Timestamp for when the value of the <code>state</code> parameter was changed.
createdAt	Timestamp for when the user account was created
updatedAt	Timestamp for when the user account was last modified
outputHomeDir	Home directory where the user's generated results are written
fileUploadPath	Path on backend datastore where files uploaded from the user's desktop are stored for use as imported datasets.
lastLoginTime	Timestamp for when the user last logged in to the product.
awsConfig	(If AWS integration is enabled) Value contains the S3 credentials, default bucket, and any extra buckets to which the user has access

For more information on roles, see *Manage Users*.