

API ImportedDatasets Post AddToFlow v4

✔ This is the latest version of the APIs.

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Add the specified imported dataset to a flow based on its internal identifier.

i NOTE: Datasets can be added to flows based on the permissions of the access token used on this endpoint. Datasets can be added to flows that are shared by the user.

Version: v4

Required Permissions

i NOTE: Each request to the Designer Cloud powered by Trifacta® platform must include authentication credentials. See <https://api.trifacta.com/ee/6.0/index.html#section/Authentication>.

Request

Request Type: POST

Endpoint:

```
/v4/importedDatasets/<id>/addToFlow
```

where:

Parameter	Description
<id>	Internal identifier for the imported dataset

Request URI - Example:

```
/v4/importedDatasets/18/addToFlow
```

Request Body:

```
{
  "flow": {
    "id": 12
  }
}
```

Response

Response Status Code - Success: 201 - Created

Response Body:

```
{
  "id": 47,
  "wrangled": false,
  "updatedAt": "2019-02-12T00:51:59.961Z",
  "createdAt": "2019-02-12T00:51:59.931Z",
  "referenceInfo": null,
  "activeSample": {
    "id": 52
  },
  "creator": {
    "id": 1
  },
  "updater": {
    "id": 1
  },
  "recipe": {
    "id": 37
  },
  "referencedFlowNode": null,
  "flow": {
    "id": 12
  }
}
```

Reference

Property	Description
id	Internal identifier for the new wrangled dataset.
wrangled	This value is always <code>true</code> .
updatedAt	Timestamp for when the dataset was updated.
createdAt	Timestamp for when the dataset was created.
referenceInfo	Reference information for the new object in the flow. Since the dataset has just been added, this value should be <code>null</code> .
activeSample.id	Internal identifier for the currently active sample for the dataset. If <code>null</code> , there is no currently active sample for the dataset.
creator.id	Internal identifier of the user who created the flow.
updater.id	Internal identifier of the user who performed the update.
recipe.id	Internal identifier for the recipe for the dataset. If <code>null</code> , the dataset has not been wrangled in the Transformer page and does not have initial parsing steps.
referencedFlowNode	Internal identifier of the node of the flow that this dataset references. Since this dataset is an imported dataset, there is no reference. This value should be <code>null</code> .
flow.id	Internal identifier of the flow that contains this dataset.

For more information on the other properties, see *API ImportedDatasets Get v4*.