

# Change Database Passwords for MySQL

**!** You should change the passwords for the Trifacta® databases immediately after installing the software.

Please complete the following steps to change the passwords for the Designer Cloud powered by Trifacta platform users of the Trifacta databases.

## Change in Database Server

1. If you have not done so already, switch to the MySQL user and launch:

```
sudo su - mysql
mysql
```

2. For each database, change the default password. Default usernames are listed for each database. Please modify the command if you are using different roles and insert a more secure password for <new\_pwd>:

**i** **NOTE:** In MySQL, the dash is a forbidden character in usernames. Please use underscores instead.

```
ALTER USER 'trifacta'@'localhost' IDENTIFIED BY '<new_pwd>';
ALTER USER 'trifactaactiviti'@'localhost' IDENTIFIED BY '<new_pwd>';
ALTER USER 'trifactatimebasedtriggerservice'@'localhost' IDENTIFIED BY '<new_pwd>';
ALTER USER 'trifactaschedulingservice'@'localhost' IDENTIFIED BY '<new_pwd>';
ALTER USER 'trifactaconfigurationsservice'@'localhost' IDENTIFIED BY '<new_pwd>';
```

3. Exit:

```
\q
exit
```

## Change in Trifacta configuration

1. Below are the username and password properties for each database. You can apply this change through the *Admin Settings Page* (recommended) or `trifacta-conf.json`. For more information, see *Platform Configuration Methods*. Please review and update as needed:

- a. **Trifacta database:**

```
"webapp.database.username" = "<user>",
"webapp.database.password" = "<pwd>",
```

- b. **Jobs database:**

```
"batch-job-runner.database.username" = "<user>",
"batch-job-runner.database.password" = "<pwd>",
```

- c. **Scheduling database:**

```
"scheduling-service.database.user" = "<user>",  
"scheduling-service.password.password" = "<pwd>",
```

**d. Time-based trigger database:**

```
"time-based-trigger-service.database.user" = "<user>",  
"time-based-trigger-service.database.password" = "<pwd>",
```

**e. Configuration Service database:**

```
"configuration-service.database.user" = "<user>",  
"configuration-service.database.password" = "<pwd>",
```

**f. Artifact Storage Service database:**

```
"artifact-storage-service.database.user" = "<user>",  
"artifact-storage-service.database.password" = "<pwd>",
```

2. Save your changes and restart the platform.