

# API Deployments Run v3

## Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

---

Run the job for the active release of the specified deployment.

- At least one manual output must be specified for the main flow within the package. See *Flow View Page*.
- An active release must be specified for the deployment. See *API Releases Patch v3*.

**i NOTE:** Deployments pertain to Production instances of the Designer Cloud powered by Trifacta® platform . For more information, see *Overview of Deployment Management*.

**Version:** v3

## Required Permissions

**i NOTE:** Each request to the Designer Cloud powered by Trifacta® platform must include authentication credentials. See <https://api.trifacta.com/ee/5.1/index.html#section/Authentication>.

## Request

**Request Type:** POST

## Endpoint:

```
/v3/deployments/<id>/run
```

where:

Parameter	Description
<id>	Internal identifier for the deployment

## Request URI - Example:

```
/v3/deployments/4/run
```

## Request Body:

Empty.

## Response

**Response Status Code - Success:** 201 - Created

## Response Body Example:

```
{
  "data": [
    {
      "reason": "JobStarted",
      "sessionId": "dd6a90e0-c353-11e7-ad4e-7f2dd2ae4621",
      "id": 33,
      "jobs": {
        "data": [
          {
            "id": 68
          },
          {
            "id": 69
          },
          {
            "id": 70
          }
        ]
      }
    }
  ]
}
```

## Reference

Property	Description
reason	Action undertaken on the endpoint.
sessionId	Internal identifier for the session of the job run
id	JobGroup identifier. For more information, see <i>API JobGroups Get v3</i> .
jobs.data.id	Internal identifier for the individual jobs that compose the job group being executed.