

API Deployments Get v4

✔ This is the latest version of the APIs.

Contents:

- *Required Permissions*
- *Request*
- *Response*
- *Reference*

Get the specified deployment.

i NOTE: Deployments pertain to Production instances of the Designer Cloud powered by Trifacta® platform . For more information, see *Overview of Deployment Manager*.

Version: v4

Required Permissions

i NOTE: Each request to the Designer Cloud powered by Trifacta® platform must include authentication credentials. See <https://api.trifacta.com/ee/6.0/index.html#section/Authentication>.

Request

Request Type: GET

Endpoint:

```
/v4/deployments/<id>
```

where:

Parameter	Description
<id>	Internal identifier for the deployment

Request URI - Example:

```
/v4/deployments/1
```

Request Body:

None.

Response

Response Status Code - Success: 200 - OK

Response Body Example:

```
{
  "id": 1,
  "name": "Test Deployment",
  "createdAt": "2019-02-13T20:14:48.537Z",
  "updatedAt": "2019-02-13T20:14:48.537Z",
  "creator": {
    "id": 7
  },
  "updater": {
    "id": 7
  }
}
```

Reference

Property	Description
id	Internal identifier for the deployment
name	Display name for the deployment. This value appears in the user interface.
createdAt	Timestamp for when the deployment was created.
updatedAt	Timestamp for when the deployment was last updated.
creator.id	Internal identifier for the user who created the deployment.
updater.id	Internal identifier for the user who last updated the deployment.