

NEXT Function

Contents:

- *Basic Usage*
- *Syntax and Arguments*
 - *col_ref*
 - *k_integer*
- *Examples*
 - *Example - Examine prior order history*

Extracts the value from a column that is a specified number of rows after the current value.

- The row from which to extract a value is determined by the order in which the rows are organized at the time that the transform is executed. If you are working on a randomly generated sample of your dataset, the values that you see for this function might not correspond to the values that are generated on the full dataset during job execution.
- If the next value is missing or null, this function generates a missing value.
- You can use the `group` and `order` parameters to define the groups of records and the order of those records to which this transform is applied.
- This function works with the following transforms:
 - *Window Transform*
 - *Set Transform*
 - *Derive Transform*

Basic Usage

```
window value:NEXT(myNumber, 1) order:Date
```

Output: Generates the new column, which contains the value in the row in the `myNumber` column immediately after the current row when the dataset is ordered by `Date`.

Syntax and Arguments

```
window value:NEXT(col_ref, k_integer) order: order_col [group: group_col]
```

Argument	Required?	Data Type	Description
<code>col_ref</code>	Y	string	Name of column whose values are applied to the function
<code>k_integer</code>	Y	integer (positive)	Number of rows after the current one from which to extract the value

For more information on the `order` and `group` parameters, see *Window Transform*.

For more information on syntax standards, see *Language Documentation Syntax Notes*.

col_ref

Name of the column whose values are used to extract the value that is `k-integer` values after the current one.

- Multiple columns and wildcards are not supported.

Usage Notes:

Required?	Data Type	Example Value
Yes	String (column reference)	myColumn

k_integer

Integer representing the number of rows after the current one from which to extract the value.

- Value must be a positive integer. For negative values, see *PREV Function*.
- $k=1$ represents the immediately following row value.
- If k is greater than or equal to the number of values in the column, all values in the generated column are missing. If a `group` parameter is applied, then this parameter should be no more than the maximum number of rows in the groups.
- If the range provided to the function exceeds the limits of the dataset, then the function generates a null value.
- If the range of the function is valid but includes missing values, the function generates a missing, non-null value.

Usage Notes:

Required?	Data Type	Example Value
Yes	Integer	4

Examples

Tip: For additional examples, see *Common Tasks*.

Example - Examine prior order history

The following dataset contains order information for the preceding 12 months. You want to compare the current month's average against the preceding quarter.

Source:

Date	Amount
12/31/15	118
11/30/15	6
10/31/15	443
9/30/15	785
8/31/15	77
7/31/15	606
6/30/15	421
5/31/15	763
4/30/15	305
3/31/15	824
2/28/15	135

1/31/15	523
---------	-----

Transform:

Using the `ROLLINGAVERAGE` function, you can generate a column containing the rolling average of the current month and the two previous months:

```
window value: ROLLINGAVERAGE(Amount, 3, 0) order: -Date
```

Note the sign of the second parameter and the `order` parameter. The sort is in the reverse order of the `Date` parameter, which preserves the current sort order. As a result, the second parameter, which identifies the number of rows to use in the calculation, must be positive to capture the previous months.

Technically, this computation does not capture the prior quarter, since it includes the current quarter as part of the computation. You can use the following column to capture the rolling average of the preceding month, which then becomes the true rolling average for the prior quarter. The `window` column refers to the name of the column generated from the previous step:

```
window value: NEXT(window, 1) order: -Date
```

Note that the order parameter must be preserved. This new column, `window1`, contains your prior quarter rolling average:

```
rename col:window1 to:'Amount_PriorQtr'
```

You can reformat this numeric value:

```
set col:Amount_PriorQtr value:NUMFORMAT(Amount_PriorQtr, '###.00')
```

You can use the following transform to calculate the net change. This formula computes the change as a percentage of the prior quarter and then formats it as a two-digit percentage.

```
derive type:single value:NUMFORMAT(((Amount - Amount_PriorQtr) / Amount_PriorQtr) * 100, '##.##') as:'NetChangePct_PriorQtr'
```

Results:

NOTE: You might notice that there are computed values for `Amount_PriorQtr` for February and March. These values do not factor in a full three months because the data is not present. The January value does not exist since there is no data preceding it.

Date	Amount	Amount_PriorQtr	NetChangePct_PriorQtr
12/31/15	118	411.33	-71.31
11/30/15	6	435.00	-98.62
10/31/15	443	489.33	-9.47
9/30/15	785	368.00	113.32
8/31/15	77	596.67	-87.1
7/31/15	606	496.33	22.1
6/30/15	421	630.67	-33.25
5/31/15	763	421.33	81.09
4/30/15	305	494.00	-38.26
3/31/15	824	329.00	150.46

2/28/15	135	523.00	-.74.19
1/31/15	523		