

# DATE Function

## Contents:

- *Basic Usage*
  - *Syntax and Arguments*
    - *year\_integer\_col*
    - *month\_integer\_col*
    - *day\_integer\_col*
    - *date\_format\_string*
  - *Examples*
    - *Example - date and time functions*
- 

Generates a date value from three inputs of Integer type: year, month, and day.

- Source values can be Integer literals or column references to values that can be inferred as Integers.
- If any of the source values are invalid or out of range, a missing value is returned.
- This function must be nested within another function that accepts date values, such as DATEFORMAT, as arguments. See the example below.

**Wrangle vs. SQL:** This function is part of Wrangle, a proprietary data transformation language. Wrangle is not SQL. For more information, see *Wrangle Language*.

## Basic Usage

### Integer literal values:

```
dateformat(date(2015,02,15),'yyyy-MM-dd')
```

**Output:** Returns the formatted date value: 2015-02-15.

### Column reference values:

```
dateformat(date(myYear, myMonth, myDay),'MMM yyyy')
```

**Output:** Returns date values based on three columns, formatted for date.

## Syntax and Arguments

```
dateformat(date(year_integer_col,month_integer_col,day_Integer_col ),'date_format_string')
```

Argument	Required?	Data Type	Description
year_integer_col	Y	integer	Name of column or Integer literal representing the year value to apply to the function
month_integer_col	Y	integer	Name of column or Integer literal representing the month value to apply to the function
day_integer_col	Y	integer	Name of column or Integer literal representing the day value to apply to the function
date_format_string	Y	string	String literal identifying the date format to apply to the value

For more information on syntax standards, see *Language Documentation Syntax Notes*.

### **year\_integer\_col**

Integer literal or name of the column containing integer values for the year.

- Missing values for this function in the source data result in missing values in the output.
- Multiple columns and wildcards are not supported.

#### **Usage Notes:**

Required?	Data Type	Example Value
Yes	Integer (literal or column reference)	2015

### **month\_integer\_col**

Integer literal or name of the column containing integer values for the month.

- Values must be 1 or more, with a maximum value of 12.
- Missing values for this function in the source data result in missing values in the output.
- Multiple columns and wildcards are not supported.

#### **Usage Notes:**

Required?	Data Type	Example Value
Yes	Integer (literal or column reference)	4

### **day\_integer\_col**

Integer literal or name of the column containing integer values for the day.

- Values must be 1 or more, with a maximum value for any month of 31.
- Missing values for this function in the source data result in missing values in the output.
- Multiple columns and wildcards are not supported.

#### **Usage Notes:**

Required?	Data Type	Example Value
Yes	Integer (literal or column reference)	26

### **date\_format\_string**

String literal that describes how the date value is formatted.

#### **Usage Notes:**

Required?	Data Type	Example Value

Yes	String literal value	'yyyy-MM-dd'
-----	----------------------	--------------

For more information, see *DATEFORMAT Function*.

## Examples

**Tip:** For additional examples, see *Common Tasks*.

### Example - date and time functions

This example provides an overview on various date and time functions.

#### Functions:

Item	Description
DATE Function	Generates a date value from three inputs of Integer type: year, month, and day.
TIME Function	Generates time values from three inputs of Integer type: hour, minute, and second.
DATETIME Function	Generates a Datetime value from the following inputs of Integer type: year, month, day, hour, minute, and second.
DATEFORMAT Function	Formats a specified Datetime set of values according to the specified date format. Source values can be a reference to a column containing Datetime values.

#### Source:

year	month	day	hour	minute	second
2016	10	11	2	3	0
2015	11	20	15	22	30
2014	12	25	18	30	45

#### Transformation:

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	DATEFORMAT(DATE (year, month, day), 'yyyy-MM-dd')
Parameter: New column name	'fctn_date'

Transformation Name	New formula
Parameter: Formula type	Single row formula
Parameter: Formula	DATEFORMAT(TIME (hour, minute, second), 'HH-mm-ss')
Parameter: New column name	'fctn_time'

Transformation Name	New formula
---------------------	-------------

<b>Parameter: Formula type</b>	Single row formula
<b>Parameter: Formula</b>	DATEFORMAT(DATETIME (year, month, day, hour, minute, second), 'yyyy-MM-dd-HH:mm:ss')
<b>Parameter: New column name</b>	'fctn_datetime'

## Results:

**NOTE:** All inputs must be inferred as Integer type and must be valid values for the specified input. For example, month values must be integers between 1 and 12, inclusive.

year	month	day	hour	minute	second	fctn_date	fctn_time	fctn_datetime
2016	10	11	2	3	0	2016-10-11	02-03-00	2016-10-11-02:03:00
2015	11	20	15	22	30	2015-11-20	15-22-30	2015-11-20-15:22:30
2014	12	25	18	30	45	2014-12-25	18-30-45	2014-12-25-18:30:45

You can apply other date and time functions to the generated columns. For an example, see *YEAR Function*.